

DRAIN OPENERL

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Date of issue: 04/21/2020 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : 206 Drain Opener
CAS No : 1310-73-2
Formula : NaOH
Synonyms : caustic soda 50% W/W / soda lye, 50%, aqueous solution / white caustic, 50%, aqueous solution
BIG no : 21703

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Chemical intermediate
Industrial use

1.3. Details of the supplier of the safety data sheet

Superior Manufacturing
4520 Glenmeade Lane
Auburn Hills, MI 48326
866.523.5677

1.4. Emergency telephone number

Emergency number : INFO TRAC (800) 535-5053

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Skin Corr. 1B H314
Eye Dam. 1 H318
Aquatic Acute 3 H402

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS05

Signal word (GHS-US) : Danger
Hazard statements (GHS-US) : H314 - Causes severe skin burns and eye damage
H402 - Harmful to aquatic life
Precautionary statements (GHS-US) : P260 - Do not breathe mist, vapours, spray
P264 - Wash exposed skin thoroughly after handling
P273 - Avoid release to the environment
P280 - Wear protective gloves, protective clothing, eye protection, face protection
P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting
P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - IF INHALED: remove victim to fresh air and keep at rest in a position comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a POISON CENTER or doctor/physician
P363 - Wash contaminated clothing before reuse
P405 - Store locked up
P501 - Dispose of contents/container to comply with local, state and federal regulations

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

DRAIN OPENER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Full text of H-phrases: see section 16

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Sodium Hydroxide	(CAS No) 1310-73-2	50	Acute Tox. 4 (Dermal), H312 Skin Corr. 1A, H314 Eye Dam. 1, H318 Aquatic Acute 3, H402
Water	(CAS No) 7732-18-5	50	Not classified

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with laboured breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital. Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service. Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or doctor/physician.
- First-aid measures after skin contact : Wash immediately with lots of water (15 minutes)/shower. Do not apply (chemical) neutralizing agents. Remove clothing while washing. Do not remove clothing if it sticks to the skin. Cover wounds with sterile bandage. Consult a doctor/medical service. If burned surface > 10%: take victim to hospital. Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a POISON CENTER or doctor/physician.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.
- First-aid measures after ingestion : Rinse mouth with water. Immediately after ingestion: give lots of water to drink. Do not induce vomiting. Do not give activated charcoal. Do not give chemical antidote. Immediately consult a doctor/medical service. Call Poison Information Centre (www.big.be/antigif.htm). Take the container/vomit to the doctor/hospital. Ingestion of large quantities: immediately to hospital. Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : Causes severe skin burns and eye damage.
- Symptoms/injuries after inhalation : EXPOSURE TO HIGH CONCENTRATIONS: Dry/sore throat. Coughing. Irritation of the respiratory tract. Irritation of the nasal mucous membranes. FOLLOWING SYMPTOMS MAY APPEAR LATER: Possible laryngeal spasm/oedema. Risk of lung oedema. Respiratory difficulties.
- Symptoms/injuries after skin contact : Caustic burns/corrosion of the skin. Slow-healing wounds.
- Symptoms/injuries after eye contact : Corrosion of the eye tissue. Permanent eye damage. Causes serious eye damage.
- Symptoms/injuries after ingestion : Vomiting. Diarrhoea. Burns to the gastric/intestinal mucosa. Possible esophageal perforation. Bleeding of the gastrointestinal tract. Shock. AFTER ABSORPTION OF HIGH QUANTITIES: Disturbances of consciousness.
- Chronic symptoms : ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Dry skin. Skin rash/inflammation. Possible inflammation of the respiratory tract.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : EXTINGUISHING MEDIA FOR SURROUNDING FIRES: Adapt extinguishing media to the environment. Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : No unsuitable extinguishing media known.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : DIRECT FIRE HAZARD. Non combustible. INDIRECT FIRE HAZARD. Reactions involving a fire hazard: see "Reactivity Hazard".
- Explosion hazard : INDIRECT EXPLOSION HAZARD. Reactions with explosion hazards: see "Reactivity Hazard".
- Reactivity : On heating: release of corrosive gases/vapours. Absorbs the atmospheric CO₂. Violent exothermic reaction with (some) acids. Reacts with (some) metals: release of highly flammable gases/vapours (hydrogen).

DRAIN OPENER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58

5.3. Advice for firefighters

- Precautionary measures fire : Exposure to fire/heat: keep upwind. Exposure to fire/heat: consider evacuation. Exposure to fire/heat: have neighbourhood close doors and windows.
- Firefighting instructions : Cool tanks/drums with water spray/remove them into safety. Dilute toxic gases with water spray. Take account of toxic fire-fighting water. Use water moderately and if possible collect or contain it.
- Protection during firefighting : Heat/fire exposure: compressed air/oxygen apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Protective equipment : Gloves. Face-shield. Corrosion-proof suit. Large spills/in enclosed spaces: compressed air apparatus. Large spills/in enclosed spaces: gas-tight suit.
- Emergency procedures : Mark the danger area. No naked flames. Wash contaminated clothes. Large spills/in confined spaces: consider evacuation. In case of hazardous reactions: keep upwind. In case of reactivity hazard: consider evacuation.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent soil and water pollution. Prevent spreading in sewers. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Contain released substance, pump into suitable containers. Consult "Material-handling" to select material of containers. Plug the leak, cut off the supply. Dam up the liquid spill. Take account of toxic/corrosive precipitation water. Hazardous reaction: measure explosive gas-air mixture. Reaction: dilute combustible gas/vapour with water curtain. Heat exposure: dilute toxic gas/vapour with water spray.
- Methods for cleaning up : Take up liquid spill into absorbent material, e.g.: dry sand/earth or powdered limestone. Scoop absorbed substance into closing containers. See "Material-handling" for suitable container materials. Carefully collect the spill/leftovers. Small quantities of liquid spill: neutralize with acid solution. Wash away neutralized product with plentiful water. Damaged/cooled tanks must be emptied. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Comply with the legal requirements. Remove contaminated clothing immediately. Clean contaminated clothing. Handle and open the container with care. Thoroughly clean/dry the installation before use. Do not discharge the waste into the drain. Keep away from naked flames/heat. Observe very strict hygiene - avoid contact. Keep container tightly closed. Measure the concentration in the air regularly. Carry operations in the open/under local exhaust/ventilation or with respiratory protection.
- Hygiene measures : Wash exposed skin thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Comply with applicable regulations.
- Storage conditions : Keep only in the original container in a cool, well ventilated place away from : incompatible materials. Keep container closed when not in use.
- Incompatible products : Strong bases. Strong acids.
- Incompatible materials : Sources of ignition. Direct sunlight.
- Storage temperature : > 15 °C
- Heat and ignition sources : KEEP SUBSTANCE AWAY FROM: heat sources.
- Prohibitions on mixed storage : KEEP SUBSTANCE AWAY FROM: combustible materials. (strong) acids. metals.
- Storage area : Store in a dry area. Keep container in a well-ventilated place. Keep locked up. Protect against frost. Provide for a tub to collect spills. Unauthorized persons are not admitted. Meet the legal requirements.
- Special rules on packaging : SPECIAL REQUIREMENTS: hermetical. dry. clean. correctly labelled. meet the legal requirements. Secure fragile packagings in solid containers.
- Packaging materials : SUITABLE MATERIAL: stainless steel. nickel. polyethylene. polypropylene. glass. stoneware/porcelain. MATERIAL TO AVOID: lead. aluminium. copper. tin. zinc. bronze.

DRAIN OPENER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Sodium Hydroxide, 50% w/w (1310-73-2)		
USA ACGIH	ACGIH Ceiling (mg/m ³)	2 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	2 mg/m ³

Sodium Hydroxide (1310-73-2)		
USA ACGIH	ACGIH Ceiling (mg/m ³)	2 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	2 mg/m ³

8.2. Exposure controls

Appropriate engineering controls	: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide adequate general and local exhaust ventilation.
Personal protective equipment	: Avoid all unnecessary exposure.
Materials for protective clothing	: GIVE GOOD RESISTANCE: butyl rubber. natural rubber. neoprene. nitrile rubber. polyethylene. PVC. tetrafluoroethylene. viton. GIVE LESS RESISTANCE: chlorinated polyethylene. styrene-butadiene rubber. nitrile rubber/PVC. GIVE POOR RESISTANCE: PVA. natural fibres.
Hand protection	: Wear protective gloves.
Eye protection	: Chemical goggles or face shield. Face shield.
Skin and body protection	: Corrosion-proof clothing.
Respiratory protection	: Wear gas mask with filter type B if conc. in air > exposure limit. Wear appropriate mask.
Other information	: Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Molecular mass	: 40.00 g/mol
Colour	: Colourless.
Odour	: Odourless.
Odour threshold	: No data available
pH	: 14 (50 %)
pH solution	: 50 %
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: 12 °C
Freezing point	: No data available
Boiling point	: 143 °C
Flash point	: Not applicable
Self ignition temperature	: Not applicable
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: 1.2 hPa
Relative vapour density at 20 °C	: No data available
Relative density	: 1.5
Density	: 1525 kg/m ³
Solubility	: Exothermically soluble in water. Soluble in ethanol. Soluble in methanol. Soluble in glycerol. Water: Complete
Log Pow	: -3.88 (Estimated value)
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 0.04 Pa.s (30 °C)
Explosive properties	: Not applicable.
Oxidising properties	: None.
Explosive limits	: No data available

DRAIN OPENER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58

9.2. Other information

Minimum ignition energy : Not applicable
VOC content : Not applicable
Other properties : Clear. Hygroscopic. Slightly volatile. Substance has basic reaction.

SECTION 10: Stability and reactivity

10.1. Reactivity

On heating: release of corrosive gases/vapours. Absorbs the atmospheric CO₂. Violent exothermic reaction with (some) acids. Reacts with (some) metals: release of highly flammable gases/vapours (hydrogen).

10.2. Chemical stability

Stable under normal conditions. Absorbs the atmospheric CO₂. Hygroscopic. Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. metals.

10.6. Hazardous decomposition products

Sodium oxide. Thermal decomposition generates : Corrosive vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Sodium Hydroxide (1310-73-2)

LD50 dermal rabbit	1350 mg/kg (Rabbit; Literature,Rabbit; Literature)
--------------------	--

Water (7732-18-5)

LD50 oral rat	≥ 90000 mg/kg
---------------	---------------

Skin corrosion/irritation : Causes severe skin burns and eye damage.
pH: 14 (50 %)

Serious eye damage/irritation : Causes serious eye damage.
pH: 14 (50 %)

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified
Based on available data, the classification criteria are not met

Carcinogenicity : Not classified

Reproductive toxicity : Not classified
Based on available data, the classification criteria are not met

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified
Based on available data, the classification criteria are not met

Aspiration hazard : Not classified
Based on available data, the classification criteria are not met

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

Symptoms/injuries after inhalation : EXPOSURE TO HIGH CONCENTRATIONS: Dry/sore throat. Coughing. Irritation of the respiratory tract. Irritation of the nasal mucous membranes. FOLLOWING SYMPTOMS MAY APPEAR LATER: Possible laryngeal spasm/oedema. Risk of lung oedema. Respiratory difficulties.

Symptoms/injuries after skin contact : Caustic burns/corrosion of the skin. Slow-healing wounds.

Symptoms/injuries after eye contact : Corrosion of the eye tissue. Permanent eye damage. Causes serious eye damage.

Symptoms/injuries after ingestion : Vomiting. Diarrhoea. Burns to the gastric/intestinal mucosa. Possible esophageal perforation. Bleeding of the gastrointestinal tract. Shock. AFTER ABSORPTION OF HIGH QUANTITIES: Disturbances of consciousness.

Chronic symptoms : ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Dry skin. Skin rash/inflammation. Possible inflammation of the respiratory tract.

DRAIN OPENER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Classification concerning the environment: not applicable.
Ecology - water : Mild water pollutant (surface water). Ground water pollutant. Maximum concentration in drinking water: 200 mg/l (sodium) (Directive 98/83/EC). Harmful to fishes. Harmful to invertebrates (Daphnia). pH shift.

Sodium Hydroxide, 50% w/w (1310-73-2)	
LC50 fishes 1	45.4 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
LC50 other aquatic organisms 1	100 mg/l (48 h; Daphnia magna; PURE SUBSTANCE)
LC50 fish 2	189 mg/l (48 h; Leuciscus idus)
TLM fish 1	125 ppm (96 h; Gambusia affinis; PURE SUBSTANCE)
TLM fish 2	99 mg/l (48 h; Lepomis macrochirus; PURE SUBSTANCE)
Threshold limit other aquatic organisms 1	100 mg/l (48 h; Daphnia magna; PURE SUBSTANCE)

Sodium Hydroxide (1310-73-2)	
LC50 fishes 1	45.4 mg/l (96 h; Salmo gairdneri (Oncorhynchus mykiss); SOLUTION >=50%)
EC50 Daphnia 1	40.4 mg/l (48 h; Ceriodaphnia sp.; NOMINAL CONCENTRATION)
LC50 fish 2	189 mg/l (48 h; Leuciscus idus)
TLM fish 1	99 mg/l (48 h; Lepomis macrochirus)
TLM fish 2	125 ppm (96 h; Gambusia affinis)

12.2. Persistence and degradability

Sodium Hydroxide, 50% w/w (1310-73-2)	
Persistence and degradability	Biodegradability: not applicable. No (test)data on mobility of the components of the mixture available.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

Sodium Hydroxide (1310-73-2)	
Persistence and degradability	Biodegradability: not applicable. No (test)data on mobility of the substance available.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

12.3. Bioaccumulative potential

Sodium Hydroxide, 50% w/w (1310-73-2)	
Log Pow	-3.88 (Estimated value)
Bioaccumulative potential	Bioaccumulation: not applicable.

Sodium Hydroxide (1310-73-2)	
Bioaccumulative potential	Bioaccumulation: not applicable.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Remove waste in accordance with local and/or national regulations. Remove for physico-chemical/biological treatment. Do not discharge into surface water.
Additional information : LWCA (the Netherlands): KGA category 05. Hazardous waste according to Directive 2008/98/EC.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT

14.1. UN number

UN-No.(DOT) : 1824
DOT NA no. UN1824

DRAIN OPENER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58

14.2. UN proper shipping name

DOT Proper Shipping Name : Sodium hydroxide solution
Department of Transportation (DOT) Hazard Classes : 8 - Class 8 - Corrosive material 49 CFR 173.136
Hazard labels (DOT) : 8 - Corrosive substances



Packing group (DOT) : II - Medium Danger
DOT Special Provisions (49 CFR 172.102) : B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized.
IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
N34 - Aluminum construction materials are not authorized for any part of a packaging which is normally in contact with the hazardous material.
T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)
TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $95 / (1 + a (tr - tf))$ Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: $a = (d15 - d50) / 35 * d50$ Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.
DOT Packaging Exceptions (49 CFR 173.xxx) : 154
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 242

14.3. Additional information

Other information : No supplementary information available.
State during transport (ADR-RID) : as liquid.

Overland transport

Packing group (ADR) : II
Class (ADR) : 8 - Corrosive substances
Hazard identification number (Kemler No.) : 80
Classification code (ADR) : C5
Danger labels (ADR) : 8 - Corrosive substances



Orange plates : 

Tunnel restriction code : E

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other : 52 - Stow "separated from" acids
EmS-No. (1) : F-A
EmS-No. (2) : S-B

Air transport

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 1 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 30 L

DRAIN OPENER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58

SECTION 15: Regulatory information

15.1. US Federal regulations

Sodium Hydroxide, 50% w/w (1310-73-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

RQ (Reportable quantity, section 304 of EPA's List of Lists) : 1000 lb

SARA Section 311/312 Hazard Classes Immediate (acute) health hazard

Sodium Hydroxide (1310-73-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

RQ (Reportable quantity, section 304 of EPA's List of Lists) : 1000 lb

SARA Section 311/312 Hazard Classes Immediate (acute) health hazard

15.2. International regulations

CANADA

Sodium Hydroxide, 50% w/w (1310-73-2)

Listed on the Canadian DSL (Domestic Substances List) inventory.

WHMIS Classification Class E - Corrosive Material

Sodium Hydroxide (1310-73-2)

Listed on the Canadian DSL (Domestic Substances List) inventory.

WHMIS Classification Class E - Corrosive Material

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC or 1999/45/EC

C; R35

Full text of R-phrases: see section 16

15.2.2. National regulations

Sodium Hydroxide, 50% w/w (1310-73-2)

Listed on the Canadian Ingredient Disclosure List

Sodium Hydroxide (1310-73-2)

Listed on the Canadian Ingredient Disclosure List

15.3. US State regulations

Sodium Hydroxide (1310-73-2)

SECTION 16: Other information

Indication of changes : Revision - See : *

Other information : None.

Full text of H-phrases: see section 16:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Aquatic Acute 3	Hazardous to the aquatic environment — Acute Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Skin Corr. 1A	Skin corrosion/irritation, Category 1A
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H402	Harmful to aquatic life

DRAIN OPENER

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58

NFPA health hazard


: 3 - Short exposure could cause serious temporary or residual injury even though prompt medical attention was given.

NFPA fire hazard

: 0 - Materials that will not burn.

NFPA reactivity

: 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently.



HMIS III Rating

Health

: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability

: 0 Minimal Hazard

Physical

: 1 Slight Hazard

Personal Protection

: H

SDS US (GHS HazCom 2012)

Information in this SDS is from available published sources and is believed to be accurate. No warranty, express or implied, is made and Tri-Chem Corporation assumes no liability resulting from the use of this SDS. The user must determine suitability of this information for his or her application.