# SAFETY DATA SHEET

## SUPERIOR MANUFACTURING

# **Section 1. Identification**

Product code     : 8123       Other means of     : OILY FLOOR PRIMER PART A
Product type : EPOXY RESIN
RESIN FOR EPOXY FLOORING, SEALING AND PATCHING
Identified uses :

Supplier's details	:	Superior Manufacturing 4520 Glenmeade Lane Auburn Hills, MI 48326
		www.ordersuperior.com info@ordersuperior.com
		866.523.5677
Emergency telephone		800.535.5053

Emergency telephone	11
number (with hours of	
operation)	

# Section 2. Hazards identification

OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	<ul> <li>SKIN CORROSION/IRRITATION - Category 2 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A SKIN SENSITIZATION - Category 1 AQUATIC HAZARD (LONG-TERM) - Category 2</li> </ul>
GHS label elements Hazard pictograms	
Signal word	: Warning
Hazard statements	<ul> <li>H319 - Causes serious eye irritation.</li> <li>H315 - Causes skin irritation.</li> <li>H317 - May cause an allergic skin reaction.</li> <li>H411 - Toxic to aquatic life with long lasting effects.</li> </ul>

#### **Precautionary statements**

## Section 2. Hazards identification

Prevention	<ul> <li>P280 - Wear protective gloves. Wear eye or face protection.</li> <li>P273 - Avoid release to the environment.</li> <li>P261 - Avoid breathing vapor.</li> <li>P264 - Wash hands thoroughly after handling.</li> <li>P272 - Contaminated work clothing should not be allowed out of the workplace.</li> </ul>
Response	<ul> <li>P391 - Collect spillage.</li> <li>P302 + P352 + P362-2 + P363 - IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse.</li> <li>P333 + P313 - If skin irritation or rash occurs: Get medical attention.</li> <li>P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.</li> <li>Remove contact lenses, if present and easy to do. Continue rinsing.</li> <li>P337 + P313 - If eye irritation persists: Get medical attention.</li> </ul>
Storage	: Not applicable.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Hazards not otherwise classified (HNOC)	: None known.

## Section 3. Composition/information on ingredients

Substance/	'mixture

: Mixture

#### CAS number/other identifiers

CAS number	: Not applicable.		
Ingredient name		%	CAS number
Epoxy Resin Cashew, nutshell liq., glycidyl ethers Phenol, polymer with formaldehyde, glyc		60 - 100 10 - 30 10 - 30	25068-38-6 171263-25-5 28064-14-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

#### Description of necessary first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 20 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Maintain an open airway. Get medical attention if symptoms occur.
Skin contact	: Wash with plenty of soap and water. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 20 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention if symptoms occur.



# Section 4. First aid measures

Most important symptoms/e	ffects, acute and delayed
Potential acute health effe	<u>ts</u>
Eye contact	: Causes serious eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation. May cause an allergic skin reaction.
Ingestion	: Irritating to mouth, throat and stomach.
<u>Over-exposure signs/symp</u>	<u>toms</u>
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Adverse symptoms may include the following: irritation redness
Ingestion	: No known significant effects or critical hazards.
Indication of immediate me	ical attention and special treatment needed, if necessary
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds
Special protective actions for fire-fighters	: No special measures are required.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	: Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.
Methods and materials for co	ntainment and cleaning up
Spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

## Precautions for safe handling

recoulding for suit numaring	
Protective measures	: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

#### Control parameters

Occupational exposure limits None.

Appropriate	engineering	ł
controls		

Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

# Section 8. Exposure controls/personal protection

Environmental exposure	1	Emissions from ventilation or work process equipment should be checked to ensure
controls		they comply with the requirements of environmental protection legislation.

Individual protection measures

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Use a properly fitted, air-purifying or supplied air respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

# **Section 9. Physical and chemical properties**

Appearance		
Physical state	: Liquid. [Viscous.]	
Color	: Colored.	
Odor	: Phenolic. [Slight]	
Odor threshold	: Not available.	
рН	: Not available.	
Melting point	: Not available.	
Boiling point	: >93.333°C (>200°F)	
Flash point	: Closed cup: >93.3°C (>199.9°F) [Setaflash.]	
Evaporation rate	: <1 (Butyl acetate = 1)	
Flammability (solid, gas)	: Not available.	
Lower and upper explosive (flammable) limits	: Not available.	
Vapor pressure	: 0.012 kPa (0.09 mm Hg) [room temperature]	
Vapor density	: >1 [Air = 1]	
Relative density	: 1.13	
Solubility	: Negligible in water.	
Partition coefficient: n- octanol/water	: Not available.	



Tel : +1-888-GHS-7769 (447-7769) / +1-450-GHS-7767 (447-7767) www.kmkregservices.com www.askdrluc.com www.ghssmart.com

# Section 9. Physical and chemical properties

Auto-ignition temperature	4	Not available.
Decomposition temperature	1	Not available.
Viscosity	1	Not available.
Volatility	1	0% (v/v)

## Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Excessive heat.
Incompatible materials	: Reactive or incompatible with the following materials: Strong Acids, Bases, Amines, Mercaptans.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Section 11. Toxicological information

## Information on toxicological effects

### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Reaction product: Bisphenol A- (epichlorhydrin)	LD50 Oral	Rat	11.4 g/kg	-
Phenol, polymer with formaldehyde, glycidyl ether	LD50 Dermal	Rat	>2000 mg/kg	-
giyolayi etilel	LD50 Oral	Rat	>2000 mg/kg	-

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Reaction product: Bisphenol A- (epichlorhydrin)	Skin - Moderate irritant	Rabbit	-	24 hours 500 μL	-
	Eyes - Mild irritant Skin - Severe irritant	Rabbit Rabbit	-	100 mg 24 hours 2 mg	-

### Sensitization

There is no data available.

#### **Carcinogenicity**

There is no data available.

Specific target organ toxicity (single exposure)

There is no data available.

Specific target organ toxicity (repeated exposure)

There is no data available.

### Aspiration hazard

There is no data available.



#### SUPERIOR MANUFACTURING

#### Section 11. Toxicological information Information on the likely : Dermal contact. Eve contact. Inhalation. Ingestion. routes of exposure Potential acute health effects Eye contact : Causes serious eye irritation. Inhalation : No known significant effects or critical hazards. **Skin contact** : Causes skin irritation. May cause an allergic skin reaction. Ingestion : Irritating to mouth, throat and stomach. Symptoms related to the physical, chemical and toxicological characteristics Eye contact : Adverse symptoms may include the following: pain or irritation watering redness Inhalation : No known significant effects or critical hazards. Skin contact Adverse symptoms may include the following: ÷. irritation redness Ingestion : No known significant effects or critical hazards. Delayed and immediate effects and also chronic effects from short and long term exposure Short term exposure **Potential immediate** : No known significant effects or critical hazards. effects **Potential delayed effects** : No known significant effects or critical hazards. Long term exposure **Potential immediate** : No known significant effects or critical hazards. effects **Potential delayed effects** : No known significant effects or critical hazards. **Potential chronic health effects** General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. Carcinogenicity : No known significant effects or critical hazards. Mutagenicity No known significant effects or critical hazards. **Teratogenicity** No known significant effects or critical hazards. 5 **Developmental effects** : No known significant effects or critical hazards. **Fertility effects** : No known significant effects or critical hazards.

## Numerical measures of toxicity

Acute toxicity estimates

There is no data available.



# Section 12. Ecological information

### **Toxicity**

There is no data available.

### Persistence and degradability

There is no data available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Reaction product: Bisphenol A- (epichlorhydrin)	-	31	low

### Mobility in soil

Soil/water partition coefficient (Koc)

: There is no data available.

#### Other adverse effects : No known significant effects or critical hazards.

## Section 13. Disposal considerations

Disposal methods	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care
	not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# Section 14. Transport information

	DOT	IMDG	IATA
UN number	UN3082	UN3082	UN3082
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Phenol, polymer with formaldehyde, glycidyl ether). Marine pollutant (Phenol, polymer with formaldehyde, glycidyl ether)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Phenol, polymer with formaldehyde, glycidyl ether). Marine pollutant (Phenol, polymer with formaldehyde, glycidyl ether)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Phenol, polymer with formaldehyde, glycidyl ether)
Transport hazard class(es)	9	9	9
Packing group	Ш	Ш	Ш
Environmental hazards	Yes.	Yes.	Yes.

# Section 14. Transport information

<u> </u>				
	I M M I I V I M I		kg.	The environmentally hazardous substance mark is not required when transported in sizes of ≤5 L or ≤5 kg.
		sizes of ≤5 L or ≤5 kg.	F-A, S-F	

#### **AERG** : 171

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to Annex II of MARPOL 73/78 and the IBC Code

## Section 15. Regulatory information

U.S. Federal regulations	: TSCA 8(a) CDR Exempt/Partial exemption: Not determined
	United States inventory (TSCA 8b): All components are listed or exempted.
Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)	: Not listed
Clean Air Act Section 602 Class I Substances	: Not listed
Clean Air Act Section 602 Class II Substances	: Not listed
DEA List I Chemicals (Precursor Chemicals)	: Not listed
DEA List I Chemicals (Precursor Chemicals)	: Not listed
SARA 302/304	
Composition/information	on ingredients
No products were found.	
SARA 304 RQ	: Not applicable.
<u>SARA 311/312</u>	
Classification	: Immediate (acute) health hazard
Composition/information	on ingredients

Name	%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
Reaction product: Bisphenol A-(epichlorhydrin)	60 - 100	No.	No.	No.	Yes.	No.
Cashew, nutshell liq., glycidyl ethers	10 - 30	No.	No.	No.	Yes.	No.
Phenol, polymer with formaldehyde, glycidyl ether	10 - 30	No.	No.	No.	Yes.	No.

#### **SARA 313**

No products were found.

#### State regulations

- Massachusetts
- New York

- : None of the components are listed.
- **ork**
- : None of the components are listed.

Tel: +1-888-GHS-7769 (447-7769) / +1-450-GHS-7767 (447-7767) www.kmkregservices.com www.askdrluc.com www.ghssmart.com

# Section 15. Regulatory information

**New Jersey** 

: None of the components are listed.

**Pennsylvania** 

: None of the components are listed.

California Prop. 65

No products were found.

# Section 16. Other information

<u>History</u> Date of issue mm/dd/yyyy Version Prepared by	7/30/2018 1 KMK Regulatory Services Inc.
Key to abbreviations	<ul> <li>ATE = Acute Toxicity Estimate</li> <li>BCF = Bioconcentration Factor</li> <li>GHS = Globally Harmonized System of Classification and Labelling of Chemicals</li> <li>IATA = International Air Transport Association</li> <li>IBC = Internediate Bulk Container</li> <li>IMDG = International Maritime Dangerous Goods</li> <li>LogPow = logarithm of the octanol/water partition coefficient</li> <li>MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)</li> <li>UN = United Nations</li> </ul>

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.



Printing date 5/15/2020

Ζ

Reviewed on 5/15/2020

#### 1 Identification

- · Product identifier
- Product Description: OILY FLOOR PRIMER (Part B)
- · Product code:
- · Application of the substance / the preparation Coating
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Superior Manufacturing 4520 Glenmeade Lane, Auburn Hills, MI 48326 ordersuperior.com 866.523.5677
- · Information department: Product safety department
- Emergency telephone number: 24 Hour Emergency: 800-535-5053

### 2 Hazard(s) identification

#### · Classification of the substance or mixture



GHS08 Health hazard

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

GHS07

- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H227 Combustible liquid.

#### · Classification according to Directive 67/548/EEC or Directive 1999/45/EC

## X Irritant

- Irritating to eyes and skin. May cause sensitisation by inhalation and skin contact.
- Information concerning particular hazards for human and environment:

The product has to be labeled due to the calculation procedure of international guidelines.

- · Classification system:
- The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

#### · Label elements

- · GHS label elements
- The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms



(Contd. on page 2)

USA

Reviewed on 5/15/2020

### Product Description: OILY FLOOR PRIMER (Part B)

		(Contd. of page 1)
· Signal word I	Danger	
<ul> <li>Hazard-deterr ethylenediamir</li> <li>Hazard staten H227 Combus H315 Causes H319 Causes H334 May cau</li> </ul>	mining components of labeling: ne nents stible liquid.	
· Precautionary		
P101 P102 P103	If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use.	
P210 P284 P261	Keep away from heat/sparks/open flames/hot surfaces No smoking In case of inadequate ventilation wear respiratory protection. Avoid breathing dust/fume/gas/mist/vapours/spray.	
P321	P338 IF IN EYES: Rinse cautiously with water for several minutes. R lenses, if present and easy to do. Continue rinsing. Specific treatment (see on this label).	
P501 • Classification	Dispose of contents/container in accordance with local/regional/natio regulations.	nal/international
· NFPA ratings		
F	Health = 1 Fire = 2 Reactivity = 0	
· HMIS-ratings	(scale 0 - 4)	
FIRE 2	Health = *1 Fire = 2 Reactivity = 0	

## 3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

#### · Dangerous components:

```
107-15-3 ethylenediamine

C R34; Xn R21/22; Xi R42/43

R10

H226; H334; H334; H314; H302; H312; H317
```

< 3.0%

### 4 First-aid measures

#### · Description of first aid measures

• After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

• After skin contact: Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)

USA

(Contd. of page 2)

# Safety Data Sheet acc. to OSHA HCS

Reviewed on 5/15/2020

#### Product Description: OILY FLOOR PRIMER (Part B)

• After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

## 5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

• Special hazards arising from the substance or mixture No further relevant information available. • Advice for firefighters

Promptly isolate the scene by removing all person from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

· Protective equipment: No special measures required.

## 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water. • Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

## 7 Handling and storage

- · Handling:
- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- · Information about protection against explosions and fires: No special measures required.
- **Conditions for safe storage, including any incompatibilities** Keep container tightly closed and in a well ventilated place.
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

(Contd. on page 4)

USA

Reviewed on 5/15/2020

#### Product Description: OILY FLOOR PRIMER (Part B)

(Contd. of page 3)

#### 8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

#### · Control parameters

#### • Components with limit values that require monitoring at the workplace:

107-15-3 ethylenediamine

PEL 25 mg/m<sup>3</sup>, 10 ppm

REL 25 mg/m<sup>3</sup>, 10 ppm

TLV 25 mg/m<sup>3</sup>, 10 ppm

Skin

• Additional information: The lists that were valid during the creation were used as basis.

#### • Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

- Avoid contact with the eyes and skin.
- · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

(Contd. on page 5)

USA

Reviewed on 5/15/2020

## Product Description: OILY FLOOR PRIMER (Part B)

(Contd. of page 4)

9 Physical and chemical prope	erties
<ul> <li>Information on basic physical and</li> <li>General Information</li> </ul>	chemical properties
· Appearance: Form:	Liquid
Color:	Light yellow
· Odor:	Amine-like
· Odour threshold:	Not determined.
· pH-value at 25 ℃ (77 ℉):	10.5
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	> 93 °C (> 199 °F)
· Flash point:	70 ℃ (158 뚜)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	
Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Not determined.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure:	Not determined.
<sup>.</sup> Density at 25 ℃ (77 ℉):	0.98977 g/cm³ (8.26 lbs/gal)
Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wat	ter): Not determined.
· Viscosity:	
Dynamic at 25 ℃ (77 ℉):	2500 cps
Kinematic:	Not determined.
• Other information	No further relevant information available.

## 10 Stability and reactivity

· Reactivity

· Chemical stability Product is stable.

• Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.

· Incompatible materials: No further relevant information available.

(Contd. on page 6)

Reviewed on 5/15/2020

#### Product Description: OILY FLOOR PRIMER (Part B)

· Hazardous decomposition products: No dangerous decomposition products known.

#### 11 Toxicological information

#### · Information on toxicological effects

- Acute toxicity:
- LD/LC50 values that are relevant for classification: Irritating to eves and skin.

#### 107 15 2 othylopodiamin

107-15-3	ethylenedi	amine
Oral	LD50	500 mg/kg (rat)
Dermal	LD50	730 mg/kg (rabbit)
Inhalative	LC50/4 h	0.3 mg/l (mouse)

- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- Sensitization:
- Sensitization possible through inhalation.
- Sensitization possible through skin contact.

#### · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

- Harmful Irritant
- · Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

#### · NTP (National Toxicology Program)

None of the ingredients is listed.

## **12 Ecological information**

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Other adverse effects No further relevant information available.

LISA

(Contd. on page 7)

(Contd. of page 5)

Reviewed on 5/15/2020

### Product Description: OILY FLOOR PRIMER (Part B)

(Contd. of page 6)

#### 13 Disposal considerations

#### · Waste treatment methods

#### · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

#### · Uncleaned packagings:

• **Recommendation:** Disposal must be made according to official regulations.

Transport information	
UN-Number DOT, ADR, IMDG, IATA	Void
UN proper shipping name DOT, ADR, IMDG, IATA	Not regulated as dangerous goods Void
Transport hazard class(es)	
DOT, IMDG, IATA Class Label	Void -
ADR Class Label	Void Miscellaneous dangerous substances and articles -
Packing group DOT, ADR, IMDG, IATA	Void
Environmental hazards: Marine pollutant:	No
Special precautions for user	Not applicable.
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	Il of Not applicable.
UN "Model Regulation":	UN-, -

## 15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture
 Sara
 Soction 355 (ovtromoly bazardous substances):

· Section 355 (extremely hazardous substances):	
107-15-3 ethylenediamine	
· Section 313 (Specific toxic chemical listings):	
None of the ingredients is listed.	
· TSCA (Toxic Substances Control Act):	
All ingredients are listed.	
(Contd. d	on page 8)
	USA

(Contd. of page 7)

# Safety Data Sheet acc. to OSHA HCS

Reviewed on 5/15/2020

## Product Description: OILY FLOOR PRIMER (Part B)

	5	
Chemicals know	own to cause cancer:	
None of the ing	predients is listed.	
· Chemicals kno	own to cause reproductive toxicity for females:	
None of the ing	predients is listed.	
· Chemicals know	own to cause reproductive toxicity for males:	
None of the ing	predients is listed.	
· Chemicals kno	own to cause developmental toxicity:	
None of the ing	predients is listed.	
· Carcinogenic	categories	
-	mental Protection Agency)	
107-15-3 ethyl	<b>U D</b>	C
TLV (Thresho	Id Limit Value established by ACGIH)	
107-15-3 ethyl	• ·	A4
NIOSH-Ca (Na	tional Institute for Occupational Safety and Health)	
•	predients is listed.	
· OSHA-Ca (Oc	cupational Safety & Health Administration)	
•	redients is listed.	
The product is Hazard pictog	classified and labeled according to the Globally Harmonized rams	System (GHS).
	anger nining components of labeling:	
ethylenediamin		
Hazard statem H227 Combust H315 Causes s H319 Causes s	ne nents tible liquid. skin irritation. serious eye irritation.	aled.
<ul> <li>Hazard statem H227 Combust H315 Causes s H319 Causes s H334 May caus H317 May caus</li> <li>Precautionary P101</li> </ul>	ne nents tible liquid. skin irritation. serious eye irritation. se allergy or asthma symptoms or breathing difficulties if inho- se an allergic skin reaction. statements If medical advice is needed, have product container or la	
Hazard statem H227 Combust H315 Causes s H319 Causes s H334 May caus H317 May caus Precautionary P101 P102	ne nents tible liquid. skin irritation. serious eye irritation. se allergy or asthma symptoms or breathing difficulties if inhere se an allergic skin reaction. <b>statements</b> If medical advice is needed, have product container or la Keep out of reach of children.	
<ul> <li>Hazard statem H227 Combust H315 Causes s H319 Causes s H334 May caus H317 May caus</li> <li>Precautionary P101 P102 P103 P210 P284</li> </ul>	ne nents tible liquid. skin irritation. serious eye irritation. se allergy or asthma symptoms or breathing difficulties if inhered se an allergic skin reaction. r statements If medical advice is needed, have product container or la Keep out of reach of children. Read label before use. Keep away from heat/sparks/open flames/hot surfaces. In case of inadequate ventilation wear respiratory protect	abel at hand. - No smoking.
<ul> <li>Hazard statem H227 Combust H315 Causes s H319 Causes s H334 May caus H317 May caus</li> <li>Precautionary P101 P102 P103 P210 P284 P261</li> </ul>	ne nents tible liquid. skin irritation. serious eye irritation. se allergy or asthma symptoms or breathing difficulties if inha- se an allergic skin reaction. r statements If medical advice is needed, have product container or la Keep out of reach of children. Read label before use. Keep away from heat/sparks/open flames/hot surfaces.	abel at hand. - No smoking. ction.

USA

# Safety Data Sheet acc. to OSHA HCS

Reviewed on 5/15/2020

#### Product Description: OILY FLOOR PRIMER (Part B)

P501

(Contd. of page 8) Dispose of contents/container in accordance with local/regional/national/international regulations.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing MSDS: Product safety department
- **Contact:** Mr Eleazar dela Cruz
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent