ICP

Novo Poxi Clear 'B'

ICP Construction Inc.

Version No: **4.7** Safety Data Sheet according to OSHA HazCom Standard (2012) requirements Issue Date: 05/28/2024 Print Date: 05/28/2024 S.GHS.USA.EN

SECTION 1 Identification

Product Identifier

Product name	Novo Poxi Clear 'B'
Synonyms	Not Available
Proper shipping name	Amines, liquid, corrosive, n.o.s. (contains isophorone diamine)
Other means of identification	Not Available

Recommended use of the chemical and restrictions on use

Relevant identified	Specialty flooring curative
uses	Specialty flooring curative

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	ICP Construction Inc.
Address	150 Dascomb Road Andover, MA 01810 United States
Telephone	1-866-667-5119 1-978-623-9987
Fax	Not Available
Website	www.icpgroup.com
Email	sds@icpgroup.com

Emergency phone number

Association / Organisation	ChemTel
Emergency telephone numbers	1-800-255-3924
Other emergency telephone numbers	1-813-248-0585

SECTION 2 Hazard(s) identification



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used

to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification	Corrosive to Metals Category 1, Acute Toxicity (Oral) Category 4, Skin Corrosion/Irritation Category 1A,
	Sensitisation (Skin) Category 1, Serious Eye Damage/Eye Irritation Category 1, Acute Toxicity (Inhalation)
	Category 4, Specific Target Organ Toxicity - Single Exposure (Narcotic Effects) Category 3, Germ Cell
	Mutagenicity Category 2, Carcinogenicity Category 2, Reproductive Toxicity Category 2, Specific Target Organ
	Toxicity - Repeated Exposure Category 2, Hazardous to the Aquatic Environment Acute Hazard Category 3,
	Hazardous to the Aquatic Environment Long-Term Hazard Category 2

Label elements



Signal word

Hazard statement(s)

May be corrosive to metals.
Harmful if swallowed.
Causes severe skin burns and eye damage.
May cause an allergic skin reaction.
Harmful if inhaled.
May cause drowsiness or dizziness.
Suspected of causing genetic defects.
Suspected of causing cancer.
Suspected of damaging fertility or the unborn child.
May cause damage to organs through prolonged or repeated exposure.
Harmful to aquatic life.
Toxic to aquatic life with long lasting effects.

Hazard(s) not otherwise classified

Not Applicable

Precautionary statement(s) General

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.
P260	Do not breathe mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.

P280	Wear protective gloves, protective clothing, eye protection and face protection.
P234	Keep only in original container.
P264	Wash all exposed external body areas thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.
P202	Do not handle until all safety precautions have been read and understood.
P272	Contaminated work clothing must not be allowed out of the workplace.

Precautionary statement(s) Response

P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If more than 15 mins from Doctor, INDUCE VOMITING (if conscious).
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/ attention.
P310	Immediately call a POISON CENTER/doctor/physician/first aider.
P312	Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P390	Absorb spillage to prevent material damage.
P391	Collect spillage.
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Precautionary statement(s) Storage

P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P406	Store in corrosive resistant/ container with a resistant inner liner.

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with
	any local regulation.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name					
100-51-6	30-60	benzyl alcohol					
135108-88-2	10-30	formaldehyde/ benzenamine, hydrogenated					
1761-71-3	3-7	4,4'-methylenebis(cyclohexylamine)					
2579-20-6	3-7	1,3-cyclohexanebis(methylamine)					

CAS No	%[weight]	Name					
128-37-0	0.5-1.5	2,6-di-tert-butyl-4-methylphenol					
1477-55-0*	5-10	m-xylenediamine					
2855-13-2*	10-30	isophorone diamine					
98-54-4*	1-5	p-tert-butylphenol					

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 First-aid measures

Description of first aid measures

Eye Contact	 If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. For amines: If liquid amines come in contact with the eyes, irrigate immediately and continuously with low pressure flowing water, preferably from an eye wash fountain, for 15 to 30 minutes. For more effective flushing of the eyes, use the fingers to spread apart and hold open the eyelids. The eyes should then be "rolled" or moved in all directions.
Skin Contact	 If skin or hair contact occurs: Immediately flush body and clothes with large amounts of water, using safety shower if available. Quickly remove all contaminated clothing, including footwear. Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. Transport to hospital, or doctor. For amines: In case of major exposure to liquid amine, promptly remove any contaminated clothing, including rings, watches, and shoe, preferably under a safety shower. Wash skin for 15 to 30 minutes with plenty of water and soap. Call a physician immediately. Remove and dry-clean or launder clothing soaked or soiled with this material before reuse. Dry cleaning of contaminated clothing may be more effective than normal laundering. Inform individuals responsible for cleaning of potential hazards associated with handling contaminated clothing. Discard contaminated leather articles such as shoes, belts, and watchbands. Note to Physician: Treat any skin burns as thermal burns. After decontamination, consider the use of cold packs and topical antibiotics.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay. Inhalation of vapours or aerosols (mists, fumes) may cause lung oedema. Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs).

Novo Poxi Clear 'B'	Print Date: 05
As this reaction may be delayed up to 24 hours after elements	exposure, affected individuals need complete rest

- (preferably in semi-recumbent posture) and must be kept under medical observation even if no symptoms are (yet) manifested.
- Before any such manifestation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered.

This must definitely be left to a doctor or person authorised by him/her.

(ICSC13719) For amines:

- All employees working in areas where contact with amine catalysts is possible should be thoroughly trained in the administration of appropriate first aid procedures.
 - · Experience has demonstrated that prompt administration of such aid can minimize the effects of accidental exposure.
- Promptly move the affected person away from the contaminated area to an area of fresh air.
- Keep the affected person calm and warm, but not hot.
- If breathing is difficult, oxygen may be administered by a qualified person.
- If breathing stops, give artificial respiration. Call a physician at once.
- For advice, contact a Poisons Information Centre or a doctor at once.
- Urgent hospital treatment is likely to be needed.
- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
 - Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.

Transport to hospital or doctor without delay.

- For amines:
 - If liquid amine are ingested, have the affected person drink several glasses of water or milk.
 - Do not induce vomiting.
 - Immediately transport to a medical facility and inform medical personnel about the nature of the exposure. The decision of whether to induce vomiting should be made by an attending physician.

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed

Clinical experience of benzyl alcohol poisoning is generally confined to premature neonates in receipt of preserved intravenous salines.

- Metabolic acidosis, bradycardia, skin breakdown, hypotonia, hepatorenal failure, hypotension and cardiovascular collapse are characteristic.
- + High urine benzoate and hippuric acid as well as elevated serum benzoic acid levels are found.
- The so-called 'gasping syndrome describes the progressive neurological deterioration of poisoned neonates.
- Management is essentially supportive.

Ingestion

- For acute or short-term repeated exposures to highly alkaline materials:
- Respiratory stress is uncommon but present occasionally because of soft tissue edema.
- · Unless endotracheal intubation can be accomplished under direct vision, cricothyroidotomy or tracheotomy may be necessary.
- Oxygen is given as indicated.
- The presence of shock suggests perforation and mandates an intravenous line and fluid administration.
- Damage due to alkaline corrosives occurs by liquefaction necrosis whereby the saponification of fats and solubilisation of proteins allow deep penetration into the tissue.

Alkalis continue to cause damage after exposure.

INGESTION:

Milk and water are the preferred diluents

No more than 2 glasses of water should be given to an adult.

- Neutralising agents should never be given since exothermic heat reaction may compound injury.
- * Catharsis and emesis are absolutely contra-indicated.

* Activated charcoal does not absorb alkali.

* Gastric lavage should not be used.

Supportive care involves the following:

- Withhold oral feedings initially.
- If endoscopy confirms transmucosal injury start steroids only within the first 48 hours.
- + Carefully evaluate the amount of tissue necrosis before assessing the need for surgical intervention.

• Patients should be instructed to seek medical attention whenever they develop difficulty in swallowing (dysphagia). SKIN AND EYE:

Injury should be irrigated for 20-30 minutes.

Eye injuries require saline. [Ellenhorn & Barceloux: Medical Toxicology]

For amines:

- Certain amines may cause injury to the respiratory tract and lungs if aspirated. Also, such products may cause tissue destruction leading to stricture. If lavage is performed, endotracheal and/or esophagoscopic control is suggested.
- No specific antidote is known.

• Care should be supportive and treatment based on the judgment of the physician in response to the reaction of the patient. Laboratory animal studies have shown that a few amines are suspected of causing depletion of certain white blood cells and their precursors in lymphoid tissue. These effects may be due to an immunosuppressive mechanism.

Some persons with hyperreactive airways (e.g., asthmatic persons) may experience wheezing attacks (bronchospasm) when exposed to airway irritants.

Lung injury may result following a single massive overexposure to high vapour concentrations or multiple exposures to lower concentrations of any pulmonary irritant material.

Health effects of amines, such as skin irritation and transient corneal edema ("blue haze," "halo effect," "glaucopsia"), are best prevented by means of formal worker education, industrial hygiene monitoring, and exposure control methods. Persons who are highly sensitive to the triggering effect of non-specific irritants should not be assigned to jobs in which such agents are used, handled, or manufactured.

Medical surveillance programs should consist of a pre-placement evaluation to determine if workers or applicants have any impairments (e.g., hyperreactive airways or bronchial asthma) that would limit their fitness for work in jobs with potential for exposure to amines. A clinical baseline can be established at the time of this evaluation.

Periodic medical evaluations can have significant value in the early detection of disease and in providing an opportunity for health counseling.

Medical personnel conducting medical surveillance of individuals potentially exposed to polyure than a mine catalysts should consider the following:

- · Health history, with emphasis on the respiratory system and history of infections
- + Physical examination, with emphasis on the respiratory system and the lymphoreticular organs (lymph nodes, spleen, etc.)
- Lung function tests, pre- and post-bronchodilator if indicated
- Total and differential white blood cell count
- Serum protein electrophoresis

Persons who are concurrently exposed to isocyanates also should be kept under medical surveillance.

Pre-existing medical conditions generally aggravated by exposure include skin disorders and allergies, chronic respiratory disease (e.g. bronchitis, asthma, emphysema), liver disorders, kidney disease, and eye disease.

Broadly speaking, exposure to amines, as characterised by amine catalysts, may cause effects similar to those caused by exposure to ammonia. As such, amines should be considered potentially injurious to any tissue that is directly contacted.

Inhalation of aerosol mists or vapors, especially of heated product, can result in chemical pneumonitis, pulmonary edema, laryngeal edema, and delayed scarring of the airway or other affected organs. There is no specific treatment.

Clinical management is based upon supportive treatment, similar to that for thermal burns.

Persons with major skin contact should be maintained under medical observation for at least 24 hours due to the possibility of delayed reactions.

Polyurethene Amine Catalysts: Guidelines for Safe Handling and Disposal Technical Bulletin June 2000 Alliance for Polyurethanes Industry

SECTION 5 Fire-fighting measures

Extinguishing media

- Foam.
- Dry chemical powder.

Special hazards arising from the substrate or mixture

Fire Incompatibility	• Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc.
	as ignition may result

Special protective equipment and precautions for fire-fighters

Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. For amines: For firefighting, cleaning up large spills, and other emergency operations, workers must wear a self-contained breathing apparatus with full face-piece, operated in a pressure-demand mode. Airline and air purifying respirators should not be worn for firefighting or other emergency or upset conditions.
Fire/Explosion Hazard	 Combustible. Slight fire hazard when exposed to heat or flame. Combustion products include: carbon dioxide (CO2) aldehydes nitrogen oxides (NOx) other pyrolysis products typical of burning organic material. May emit corrosive fumes. WARNING: Long standing in contact with air and light may result in the formation of potentially explosive peroxides.

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before discharge or disposal of material. Check regularly for spills and leaks. Slippery when spilt. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. for amines: If possible (i.e., without risk of contact or exposure), stop the leak. Contain the spilled material by diking, then neutralize.
Major Spills	 Slippery when spilt. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. For amines: First remove all ignition sources from the spill area. Have firefighting equipment nearby, and have firefighting personnel fully trained in the proper use of the equipment and in the procedures used in fighting a chemical fire.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. DO NOT allow clothing wet with material to stay in contact with skin
Other information	 Store in original containers. Keep containers securely sealed. DO NOT store near acids, or oxidising agents No smoking, naked lights, heat or ignition sources.

Conditions for safe storage, including any incompatibilities

Suitable container	 Glass container is suitable for laboratory quantities Lined metal can, lined metal pail/ can. Plastic pail. For low viscosity materials Drums and jerricans must be of the non-removable head type. Where a can is to be used as an inner package, the can must have a screwed enclosure.
Storage incompatibility	 Benzyl alcohol: may froth in contact with water slowly oxidises in air, oxygen forming benzaldehyde is incompatible with mineral acids, caustics, aliphatic amines, isocyanates reacts violently with strong oxidisers, and explosively with sulfuric acid at elevated temperatures corrodes aluminium at high temperatures is incompatible with aluminum, iron, steel attacks some nonfluorinated plastics; may attack, extract and dissolve polypropylene Benzyl alcohol contaminated with 1.4% hydrogen bromide and 1.2% of dissolved iron(II) polymerises exothermically above 100 deg. C. Amines are incompatible with: isocyanates, halogenated organics, peroxides, phenols (acidic), epoxides, anhydrides, and acid halides. strong reducing agents such as hydrides, due to the liberation of flammable gas. Avoid strong acids, acid chlorides, acid anhydrides and chloroformates. Avoid contact with copper, aluminium and their alloys. Avoid reaction with oxidising agents

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes	
US OSHA Permissible Exposure Limits (PELs) Table Z-1	2,6-di-tert-butyl-4- methylphenol	Particulates Not Otherwise Regulated (PNOR)- Respirable fraction	5 mg/m3	Not Available	Not Available	Not Available	
US OSHA Permissible Exposure Limits (PELs) Table Z-1	2,6-di-tert-butyl-4- methylphenol	Particulates Not Otherwise Regulated (PNOR)- Total dust	15 mg/m3	Not Available	Not Available	Not Available	
US OSHA Permissible Exposure Limits (PELs)	2,6-di-tert-butyl-4- methylphenol	Inert or Nuisance Dust: Total Dust	15 mg/m3 / 50 mppcf	Not Available	Not Available	Not Available	

Novo Poxi Cl	ear 'B'
--------------	---------

Source	Ingr	edient	Material nam	e	Т٧	NA	STEL	-	Peak	Notes
Table Z-3										
US OSHA Permissible Exposure Limits (PELs) Table Z-3		di-tert-butyl-4- nylphenol	Inert or Nuisa Dust: Respira		- 5		Not Availa	able	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)		6-di-tert-butyl-4- ethylphenol		tyl-p-cresol 1) mg/m3	Not Availa	able	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	m-xy	lenediamine	m-Xylene-alp diamine	ha,alpha'-	No Av	ot /ailable	Not Availa	able	0.1 mg/m3	[skin]
US OSHA Permissible Exposure Limits (PELs) Table Z-1	p-ter	t-butylphenol	Particulates N Regulated (Pl	lot Otherwise NOR)- Total dust	15	15 mg/m3		able	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	p-ter	t-butylphenol	Particulates Not Otherwise Regulated (PNOR)- Respirable fraction		5 ו	mg/m3	Not Availa	able	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	p-ter	t-butylphenol	Inert or Nuisance Dust: Total Dust			5 mg/m3 /) mppcf	Not Availa	able	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-3	p-ter	t-butylphenol	Inert or Nuisance Dust: Respirable fraction			mg/m3 / 5 mppcf	Not Availa	able	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	p-ter	t-butylphenol	Particulates not otherwise regulated		No Av	ot /ailable	Not Availa	able	Not Available	See Appendix D
Emergency Limits										
Ingredient	TEE	L-1		TEEL-2			TE	TEEL-3		
benzyl alcohol	30 p	pm		52 ppm		740	740 ppm			
p-tert-butylphenol	1.5 r	mg/m3		40 mg/m3		240 mg/m3				
Ingredient		Original IDLH	I			Revised IDLH				
benzyl alcohol	Not Available					Not Available				
formaldehyde/ benzenamine, hydrogenated Not Available					Not Available					

Not Available

Not Available

Not Available

Not Available

Not Available

Not Available

methylenebis(cyclohexylamine)

cyclohexanebis(methylamine) 2,6-di-tert-butyl-4-methylphenol

m-xylenediamine

p-tert-butylphenol

isophorone diamine

Not Available

Not Available

Not Available

Not Available

Not Available

Not Available

4,4'-

1,3-

Continued...

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit	
benzyl alcohol	E	≤ 0.1 ppm	
formaldehyde/ benzenamine, hydrogenated	E	≤ 0.1 ppm	
4,4'- methylenebis(cyclohexylamine)	E	≤ 0.1 ppm	
1,3- cyclohexanebis(methylamine)	D	> 0.1 to ≤ 1 ppm	
isophorone diamine	E	≤ 0.1 ppm	
Notes:	based on a chemical's potency and the adverse heal	upational exposure banding is a process of assigning chemicals into specific categories or bands ad on a chemical's potency and the adverse health outcomes associated with exposure. The output is process is an occupational exposure band (OEB), which corresponds to a range of exposure rentrations that are expected to protect worker health.	

Exposure controls

Appropriate engineering controls	 Unless written procedures, specific to the workplace are available, the following is intended as a guide: For Laboratory-scale handling of Substances assessed to be toxic by inhalation. Quantities of up to 25 grams may be handled in Class II biological safety cabinets *; Quantities of 25 grams to 1 kilogram may be handled in Class II biological safety cabinets* or equivalent containment systems; Quantities exceeding 1 kg may be handled either using specific containment, a hood or Class II biological safety cabinet*, HEPA terminated local exhaust ventilation should be considered at point of generation of dust, fumes or vapours.
Individual protection measures, such as personal protective equipment	
Eye and face protection	 When handling very small quantities of the material eye protection may not be required. For laboratory, larger scale or bulk handling or where regular exposure in an occupational setting occurs: Chemical goggles. For amines: SPECIAL PRECAUTION: Because amines are alkaline materials that can cause rapid and severe tissue damage, wearing of contact lenses while working with amines is strongly discouraged. Wearing such lenses can prolong contact of the eye tissue with the amine, thereby causing more severe damage.
Skin protection	See Hand protection below
Hands/feet protection	 Elbow length PVC gloves When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Rubber gloves (nitrile or low-protein, powder-free latex, latex/ nitrile). Employees allergic to latex gloves should use nitrile gloves in preference. For amines: Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly.
Body protection	See Other protection below
Other protection	► Overalls.

PVC Apron.

Respiratory protection

Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

Where engineering controls are not feasible and work practices do not reduce airborne amine concentrations below recommended exposure limits, appropriate respiratory protection should be used. In such cases, air-purifying respirators equipped with cartridges designed to protect against amines are recommended.

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Not Available		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n- octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	>93	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	<5

SECTION 10 Stability and reactivity

Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhaling corrosive bases may irritate the respiratory tract. Symptoms include cough, choking, pain and damage to the mucous membrane. Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo. Inhalation of amine vapours may cause irritation of the mucous membrane of the nose and throat, and lung irritation with respiratory distress and cough. Swelling and inflammation of the respiratory tract is seen in serious cases; with headache, nausea, faintness and anxiety. Inhalation of epoxy resin amine hardeners (including polyamines and amine adducts) may produce bronchospasm and coughing episodes lasting several days after cessation of the exposure. Even faint traces of these vapours may trigger an intense reaction in individuals showing 'amine asthma'. Inhalation of benzyl alcohol may affect breathing (causing depression and paralysis of breathing and lower blood pressure. Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful. Acute effects from inhalation of high vapour concentrations may be chest and nasal irritation with coughing, sneezing, headache and even nausea.
Ingestion	Ingestion of alkaline corrosives may produce burns around the mouth, ulcerations and swellings of the mucous membranes, profuse saliva production, with an inability to speak or swallow. Both the oesophagus and stomach may experience burning pain; vomiting and diarrhoea may follow. Amines without benzene rings when swallowed are absorbed throughout the gut. Corrosive action may cause damage throughout the gastrointestinal tract. Ingestion of amine epoxy-curing agents (hardeners) may cause severe abdominal pain, nausea, vomiting or diarrhoea. The vomitus may contain blood and mucous. The material has NOT been classified by EC Directives or other classification systems as 'harmful by ingestion'. This is because of the lack of corroborating animal or human evidence. Swallowing large doses of benzyl alcohol may cause abdominal pain, nausea, vomiting and diarrhea. It may affect behaviour and/or the central nervous system, and cause headache, sleepiness, excitement, dizziness, inco-ordination, coma, convulsions and other symptoms of central nervous system depression. Central nervous system (CNS) depression may include general discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in respiratory depression and may be fatal. Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.
Skin Contact	The material can produce severe chemical burns following direct contact with the skin.

Novo	Poxi	Clear	'B'
14040		Gieai	

If applied to the eyes, this material causes severe eye damage. Direct eye contact with corrosive bases can cause pain and burns. There may be swelling, epithelium destruction, clouding of the cornea and inflammation of the iris. Vapours of volatile amines irritate the eyes, causing excessive secretion of tears, inflammation of the conjunctiva and slight swelling of the cornea, resulting in 'halos' around lights. This effect is temporary, lasting only for a few hours. There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment. Repeated or prolonged exposure to corrosives may result in the erosion of teeth, inflammatory and ulcerative changes in the mouth and necrosis (rarely) of the jaw. Bronchial irritation, with cough, and frequent attacks of bronchial pneumonia may ensue. Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems. Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed. This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects. Ample evidence from experiments exists that there is a suspicion this material directly reduces fertility. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Prolonged or repeated exposure. Prolonged or repeated exposure. Prolonged or repeated exposure. <t< th=""><th></th><th>Amine epoxy-curing agents (hardeners) may produce primary skin irritation and sensitisation dermatitis in predisposed individuals. Cutaneous reactions include erythema, intolerable itching and severe facial swelling. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. Skin contact with alkaline corrosives may produce severe pain and burns; brownish stains may develop. The corroded area may be soft, gelatinous and necrotic; tissue destruction may be deep. Volatile amine vapours produce irritation and inflammation of the skin. Direct contact can cause burns. Skin contact with the material may be harmful; systemic effects may result following absorption. There is some evidence to suggest that the material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.</th></t<>		Amine epoxy-curing agents (hardeners) may produce primary skin irritation and sensitisation dermatitis in predisposed individuals. Cutaneous reactions include erythema, intolerable itching and severe facial swelling. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. Skin contact with alkaline corrosives may produce severe pain and burns; brownish stains may develop. The corroded area may be soft, gelatinous and necrotic; tissue destruction may be deep. Volatile amine vapours produce irritation and inflammation of the skin. Direct contact can cause burns. Skin contact with the material may be harmful; systemic effects may result following absorption. There is some evidence to suggest that the material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.
 make an assessment. Repeated or prolonged exposure to corrosives may result in the erosion of teeth, inflammatory and ulcerative changes in the mouth and necrosis (rarely) of the jaw. Bronchial irritation, with cough, and frequent attacks of bronchial pneumonia may ensue. Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems. Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed. This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects. Ample evidence from experiments exists that there is a suspicion this material directly reduces fertility. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Prolonged or repeated exposure to benzyl alcohol may cause allergic contact dermatitis (skin inflammation). Prolonged or repeated swallowing may affect behaviour and the central nervous system with symptoms similar 	Eye	Direct eye contact with corrosive bases can cause pain and burns. There may be swelling, epithelium destruction, clouding of the cornea and inflammation of the iris. Vapours of volatile amines irritate the eyes, causing excessive secretion of tears, inflammation of the conjunctiva and slight swelling of the cornea, resulting in 'halos' around lights. This effect is temporary, lasting
	Chronic	 make an assessment. Repeated or prolonged exposure to corrosives may result in the erosion of teeth, inflammatory and ulcerative changes in the mouth and necrosis (rarely) of the jaw. Bronchial irritation, with cough, and frequent attacks of bronchial pneumonia may ensue. Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems. Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed. This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects. Ample evidence from experiments exists that there is a suspicion this material directly reduces fertility. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Prolonged or repeated exposure to benzyl alcohol may cause allergic contact dermatitis (skin inflammation). Prolonged or repeated swallowing may affect behaviour and the central nervous system with symptoms similar

Novo Poxi Clear 'B'	TOXICITY IRRITATION		IRRITATION
NOVO POXI Clear B	Not Available	Not Available	
	ΤΟΧΙΟΙΤΥ	IRRITATION	
	Dermal (rabbit) LD50: 2000 mg/kg ^[2]	Eye (rabbit): 0.75 mg open SEVERE	
benzyl alcohol	Inhalation (Rat) LC50: >4.178 mg/L4h ^[2]	Eye: adverse effect observed (irritating) ^[1]	
benzyr alconor	Oral (Rat) LD50: 1230 mg/kg ^[2]	Skin (man): 16 mg/48h-mild	
		Skir	n (rabbit):10 mg/24h open-mild
		Skir	n: no adverse effect observed (not irritating) ^[1]
formaldehyde/ benzenamine,			
hydrogenated	ΤΟΧΙCΙΤΥ	IR	RITATION
	Dermal (rabbit) LD50: >1000 mg/kg ^[1]	Sł	kin: adverse effect observed (corrosive) ^[1]

	Oral (Rat) LD50: >50<300 mg/k	‹g ^[1]		
	ΤΟΧΙΟΙΤΥ	IRRITATIO	Ν	
	Dermal (rabbit) LD50: >1000 mg/kg ^[1]	Eye (rabbit): 10uL./24h SEVERE		
4,4'- methylenebis(cyclohexylamine)	Inhalation(Mouse) LC50; 0.4 mg/l4h ^[2]	Eye: adver	se effect observed (irritating) ^[1]	
	Oral (Rat) LD50: 350 mg/kg ^[1]	Skin (rabbit): SEVERE Corrosive ** * [Air Products and Chemicals] ** [BASF CCINFO 1882394]		
		Skin: adver	se effect observed (corrosive) ^[1]	
	ΤΟΧΙΟΙΤΥ		IRRITATION	
1,3-	Dermal (rabbit) LD50: 1700 mg	/kg ^[1]	Eye: adverse effect observed (irritating) ^[1]	
cyclohexanebis(methylamine)	Oral (Rat) LD50: >200<2000 m	g/kg ^[1]	Skin: adverse effect observed (corrosive) ^[1]	
	TOWOTY			
			ye (rabbit): 100 mg/24h-moderate	
2,6-di-tert-butyl-4-methylphenol			ye: no adverse effect observed (not irritating) ^[1] kin (human): 500 mg/48h - mild	
		Skin (rabbit):500 mg/48h-moderate		
			Skin: no adverse effect observed (not irritating) ^[1]	
	TOXICITY		IRRITATION	
	Dermal (rabbit) LD50: 2000 mg/kg ^[2]		Eye (rabbit): 0.05 mg/24h SEVERE	
	Inhalation (Rat) LC50: 700 ppm/1h ^[2]		Eye: adverse effect observed (irritating) ^[1]	
m-xylenediamine	Oral (Rat) LD50: 930 mg/kg ^[2]		Skin (rabbit): 0.75 mg/24h SEVERE	
			Skin: adverse effect observed (corrosive) ^[1]	
			Skin: adverse effect observed (irritating) ^[1]	
	ΤΟΧΙΟΙΤΥ	IRRIT	ATION	
isophorone diamine	Oral (Rat) LD50: 1030 mg/kg ^[2]		dverse effect observed (irreversible damage) ^[1]	
		Skin: adverse effect observed (corrosive) ^[1]		
	TOXICITY IRRITATION			
	Dermal (rabbit) LD50: 2288 mg	/kg ^[2]	Eye (rabbit) 0.05 mg/24h - SEVERE	
	Oral (Rat) LD50: 2951 mg/kg ^[2]		Eye (rabbit): 10 mg - SEVERE	
p-tert-butylphenol			Eye: adverse effect observed (irritating) ^[1]	
			Skin (rabbit): 500 mg/4h - mild	
			Skin: adverse effect observed (irritating) ^[1]	
	2			

Legend:		ed from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of tances
BEN2	ZYL ALCOHOL	Unlike benzylic alcohols, the beta-hydroxyl group of the members of benzyl alkyl alcohols contributes to break down reactions but do not undergo phase II metabolic activation. Though structurally similar to cancer causing ethyl benzene, phenethyl alcohol is only of negligible concern due to limited similarity in their pattern of activity. For benzoates: Benzyl alcohol, benzoic acid and its sodium and potassium salt have a common metabolic and excretion pathway. All but benzyl alcohol are considered to be unharmful and of low acute toxicity. This is a member or analogue of a group of benzyl derivatives generally regarded as safe (GRAS), based partly on their self-limiting properties as flavouring substances in food. In humans and other animals, they are rapidly absorbed, broken down and excreted, with a wide safety margin. The aryl alkyl alcohol (AAA) fragrance ingredients have diverse chemical structures, with similar metabolic and toxicity profiles. The AAA fragrances demonstrate low acute and
FORMALDEHYDE/ B HYI	ENZENAMINE, DROGENATED	subchronic toxicity by skin contact and swallowing. Amine adducts have much reduced volatility and are less irritating to the skin and eyes than amine hardeners. However commercial amine adducts may contain a percentage of unreacted amine and all unnecessary contact should be avoided. No significant acute toxicological data identified in literature search.
METHYLENEBIS(CYCLO	4,4'- HEXYLAMINE)	The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.
CYCLOHEXANEBIS(M	1,3-	Gastrointestinal changes recorded. For 1,3-cyclohexanebis(methylamine) (CHBM): Animal testing shows that CHBMhas low to moderate acute toxicity by swallowing and moderate acute toxicity by skin contact. It is corrosive to the eyes and skin.
,	ERT-BUTYL-4- THYLPHENOL	* Degussa SDS Effects such as behavioral changes, reduction in body weight gain, and decrement in body weight have been observed after long-term administration of BHT to mice and rats. Toxic effects may be attributed more to BHT metabolites than to their parent compound, only a few studies have focused on their carcinogenicity and toxicity, and not only on that of BHT. The metabolite BHT-QM (syn: 2,6-di-tert-butyl-1,4-methylene-2,5-cyclohexadien-1-one, CAS RN: 2607-52-5) is a very reactive compound which is considered to play a significant role in hepatoxicity, pneumotoxicity, and skin tumor promotion in mice. BHT has been reported to exert prooxidant effects under certain conditions. Thus, when BHT was added in excess to a wheat seedling medium in aerobic conditions, an enhancement of the generation rate of superoxide anion was observed. Some authors have reported that at high aeration rate, BHT can react with molecular oxygen rather than with the reactive oxygen species present, yielding BHT-phenoxyl radical and superoxide anion. In addition, the phenolic radical itself may undergo redox recycling which can be a critical factor depending on the reductant involved However, it has to be noted that BHT-phenoxyl radical has been reported to be relatively stable. Furthermore, the potential reactivity of BHT-derived metabolites should be taken into account; some studies reported that not only BHT but also its metabolites, such as BHT-Q and BHT-QM, can act as prooxidant. As BHT undergoes several reactions during biotransformation, a large number of intermediate metabolites have been identified. However, their nature and concentration depend on the environmental conditions and on the animal species. Although the changes undergone by BHT during in vivo digestion processes have not been studied, after submission of a fluid deep-frying fat containing BHT and BHT-QM to an in vitro gastrointestinal digestion model, both these were detected in the digested samples. These results indicate that BHT and its toxic metaboliter

microsomal monooxygenase system and its major route of degradation is oxidation catalyzed
by cytochrome P450. Studies have reported potential toxicity derived from the ingestion or
administration of BHT. As for acute oral toxicity, although this is considered low in animals, it
must be noted that 2 clinical cases were reported in patients who suffered acute neurotoxicity
and gastritis after ingesting a high dose of BHT (4 and 80 g without medical prescription) to
cure recurrent genital herpes. Regarding short-term subchronic toxicity studies, it has been
reported that BHT causes dose-related increase in the incidence and severity of toxic
nephrosis in mice, nephrotoxicity and pneumotoxicity in rats, and in chicken a marked
congestion of the liver and kidney, as well as diffuse enlargement of the liver with rounded
borders and rupture with hemorrhaging . It has to be noted that the EFSA Panel (2012)
pointed out certain inconsistencies in the findings obtained from the short-term and
subchronic toxicity studies. Several genotoxicity studies on BHT concluded that BHT does not
represent a genotoxic risk, because most of the studies carried out to that date had shown
BHT was not able to induce mutations or to damage deoxyribonucleic acid (DNA).
Nevertheless, it must be mentioned that other studies reported contrary results. The effect of
BHT and 7 of its metabolites on in vitro DNA cleavage was studied and the metabolites BHT-
Q (syn: 2,6-di-tert-butyl-2,5-cyclohexadiene-1,4-dione, CAS RN: 719-22-2), BHT-CHO (syn:
3,5-di-tert-butyl-4-hydroxybenzaldehyde, CAS RN: 1620-98-0 and BHT-OOH (syn: 2,6-di-tert-
butyl-4-methyl-4-hydroperoxy-2,5-cyclohexadien-1-one, CAS RN: 6485-57-0) were able to
cleave DNA The Panel on Food Additives and Nutrient Sources Added to Food of the
European Food Safety Authority (EFSA) recognized that these positive genotoxicity results
may be due to the prooxidative chemistry of BHT, which gives rise to reactive metabolites.
Some studies addressed the carcinogenicity and chronic toxicity of BHT and its metabolites in
rodents with contradictory results. Thus, mice-fed dietary BHT for a year developed marked
hyperplasia of the hepatic bile ducts with an associated subacute cholangitis Moreover, after
104 wk of administration of BHT, the formation of hepatocellular tumors in male mice was
observed. Several studies have demonstrated the potential of BHT to act either as a tumor
promotor or as a tumor suppressor, modulating the carcinogenicity of some well-known
carcinogens. Barbara Nieva-Echevarria etal: Comprehensive reviews in Food Science and
Food Safety, Vol 14, Dec 2014 https://onlinelibrary.wiley.com/doi/10.1111/1541-
4337.12121/pdf
for bridged alkyl phenols:
Acute toxicity: Acute oral and dermal toxicity data are available for all but two of the
substances in the group. The data show that acute toxicity of these substances is low.
ferroptosis inhibitors are currently being treated systemically rather than specifically, which

substances in the group. The data show that acute toxicity of these substances is low. ferroptosis inhibitors are currently being treated systemically rather than specifically, which may have multiple side effects. For example,Desferoxamin (DFO), an iron chelating agent, is known to have a short half-life, need long-term subcutaneous infusions, and provoke ototoxicity and neurotoxicity.

The substance is classified by IARC as Group 3:

NOT classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing.

Data show that acute toxicity following oral and topical use of hindered phenols is low. They are not proven to cause mutations.

Allergic reactions involving the respiratory tract are usually due to interactions between IgE antibodies and allergens and occur rapidly. Allergic potential of the allergen and period of exposure often determine the severity of symptoms.

Attention should be paid to atopic diathesis, characterised by increased susceptibility to nasal inflammation, asthma and eczema.

m-xylenediamine Exogenous allergic alveolitis is induced essentially by allergen specific immune-complexes of the IgG type; cell-mediated reactions (T lymphocytes) may be involved. Such allergy is of the delayed type with onset up to four hours following exposure.

For benzene-1,3-dimethanamine (m-xylene-alpha,alpha -diamine):

Animal testing showed that benzene-1,3-methanamine caused tissue damage to the digestive and respiratory organs, if given by mouth or inhaled, respectively. The chemical is corrosive to animal skin, and may cause sensitization.

isophorone diamine	Isophorone diamine is a strong skin irritant, corrosive with repeated application. Frequent occupational exposure may lead to the development of allergic skin inflammation. The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.
p-tert-butylphenol	These substances are intravenous anaesthetic agents. They have a very low level of acute toxicity; they may cause skin irritation. For p-tert-butylphenol: p-tert-butylphenol has low acute toxicity via all routes. It irritates the skin, eyes and airway.
Novo Poxi Clear 'B' & 2,6-DI-TERT- BUTYL-4-METHYLPHENOL	Laboratory (in vitro) and animal studies show, exposure to the material may result in a possible risk of irreversible effects, with the possibility of producing mutation.
Novo Poxi Clear 'B' & FORMALDEHYDE/ BENZENAMINE, HYDROGENATED & 4,4'- METHYLENEBIS(CYCLOHEXYLAMINE) & 1,3- CYCLOHEXANEBIS(METHYLAMINE) & 2,6-DI-TERT-BUTYL-4- METHYLPHENOL & m-xylenediamine & isophorone diamine & p-tert- butylphenol	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound.
Novo Poxi Clear 'B' & BENZYL ALCOHOL	Adverse reactions to fragrances in perfumes and fragranced cosmetic products include allergic contact dermatitis, irritant contact dermatitis, sensitivity to light, immediate contact reactions, and pigmented contact dermatitis. Airborne and connubial contact dermatitis occurs. Fragrance allergens act as haptens, low molecular weight chemicals that cause an immune response only when attached to a carrier protein. However, not all sensitizing fragrance chemicals are directly reactive, but require previous activation.
Novo Poxi Clear 'B' & 4,4'- METHYLENEBIS(CYCLOHEXYLAMINE) & m-xylenediamine	Overexposure to most of these materials may cause adverse health effects. Many amine-based compounds can cause release of histamines, which, in turn, can trigger allergic and other physiological effects, including constriction of the bronchi or asthma and inflammation of the cavity of the nose. Whole-body symptoms include headache, nausea, faintness, anxiety, a decrease in blood pressure, rapid heartbeat, itching, reddening of the skin, urticaria (hives) and swelling of the face, which are usually transient. There are generally four routes of possible or potential exposure: inhalation, skin contact, eye contact, and swallowing. Inhalation: Inhaling vapours may result in moderate to severe irritation of the tissues of the nose and throat and can irritate the lungs.
BENZYL ALCOHOL & 4,4'- METHYLENEBIS(CYCLOHEXYLAMINE) & 1,3- CYCLOHEXANEBIS(METHYLAMINE) & 2,6-DI-TERT-BUTYL-4- METHYLPHENOL & m-xylenediamine & isophorone diamine	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema.
BENZYL ALCOHOL & 4,4'- METHYLENEBIS(CYCLOHEXYLAMINE) & 2,6-DI-TERT-BUTYL-4- METHYLPHENOL & isophorone diamine & p-tert-butylphenol	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.
4,4'- METHYLENEBIS(CYCLOHEXYLAMINE)	The material may produce respiratory tract irritation, and result in damage to the lung including reduced lung function.

CYCLOHEXANEBIS(MET	HYLAMINE) & orone diamine				
1,3- CYCLOHEXANEBIS(METHYLAMINE) & m-xylenediamine & p-tert-butylphenol		The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.			
CYCLOHEXANEBIS(MET	1,3- THYLAMINE) & xylenediamine	The material may cause severe skin irritation after p produce on contact skin redness, swelling, the prod of the skin. Repeated exposures may produce seve	uction of vesicles, scaling and thickening		
Acute Toxicity	~	Carcinogenicity	✓		
Skin Irritation/Corrosion	~	Reproductivity	~		
Serious Eye Damage/Irritation	*	STOT - Single Exposure	v		
Respiratory or Skin sensitisation	*	STOT - Repeated Exposure	v		
Mutagenicity	~	Aspiration Hazard	×		

Legend:

Data either not available or does not fill the criteria for classification
 Data available to make classification

SECTION 12 Ecological information

Toxicity

	Endpoint	Test Duration (hr)	Species	Valu	ie	Source	9	
Novo Poxi Clear 'B'	Not Available	Not Available Not Available				t Available Not Ava		ailable	
	Endpoint	Test Duration (hr)) Spe	ecies			Value	Source	
	EC50	72h	72h Algae or other aquatic p		ic plant	s	500mg/l	2	
	LC50	96h	Fish	า			10mg/l	2	
benzyl alcohol	EC50	48h	Cru	stacea			230mg/l	2	
	NOEC(ECx)	336h	Fish	า			5.1mg/l	2	
	EC50	96h	Alg	ae or other aquat	ic plant	S	76.828mg/l	2	
	1							1	
	Endpoint	Test Duration (hr)	Spe	ecies			Value	Source	
	LC50	96h	Fish	Fish		63mg/l		2	
formaldehyde/ benzenamine, hydrogenated	EC50	72h	Alga	Algae or other aquatic plan		ts 43.94mg/l		2	
nyurogenateu	EC50	48h	Crustacea			15.4mg/l		2	
	EC10(ECx)	72h	Alga	ae or other aquat	ic plant	s	1.2mg/l	2	
							1		
	Endpoint	Test Duration (hr)	Specie	S		Value		Source	
	LC50	96h	Fish	Fish		68mg/l		2	
4,4'- methylenebis(cyclohexylamine)	EC50	72h	Algae c	Algae or other aquatic plants		>=141.42<=200mg/l		2	
meny mobile (oy cronexy anime)	EC50	48h	Crustad	cea		6.84mg	g/l	2	
	NOEC(ECx)	336h	Fish			>1mg/l		2	

	Endpoint	Test Duration (hr	.)	Species		Value		Source
	EC50	72h		Algae or other aquatic plants		29.7mg/l		2
1,3 cyclohexanebis(methylamine	L L C50	96h		Fish		130mg	/I	2
Cyclonexanebis(methylanini	NOEC(ECx)	72h	Algae or other aquatic		tic plants		g/I	2
	EC50	EC50 48h		Crustacea		33.1mg	g/I	2
	Endpoint	Test Duration (hr)	Spe	cies Val		lue Sou		rce
	ErC50	72h		Algae or other aquatic plants		mg/l	1	
2,6-di-tert-butyl-4-methylphenol	LC50	96h	Fish		>0.5m	ng/l	Not Available	
	BCF	1344h	Fish		220-2	-	7	
	EC50	72h	Alga	e or other aquatic plants	>0.42		1	
	EC50	48h		stacea	>0.17	ma/l	2	
	EC0(ECx)	48h	Crus	stacea	>=0.3		1	
	EC50	96h	-	e or other aquatic plants	0.758		2	
			1.3		000		_	
	Endpoint	Test Duration (hr	.)	Species		Value		Source
	EC50	72h		Algae or other aquatic plants		12mg/l		2
m-xylenediamine	EC50	48h		Crustacea		15.2mg/l		2
	NOEC(ECx)	504h		Crustacea		4.7mg/	1	2
	LC50	96h		Fish		75mg/l		2
	BCF	1008h		Fish		<0.3		7
		1						
	Endpoint	Test Duration (hr)	S	Species		lue		Source
	BCF	1008h	Fi	Fish <		.3		7
· · · · · · · · · · · · · · · · · · ·	LC50	96h	Fi	Fish 7		′0mg/l		1
isophorone diamir	NOEC(ECx)	72h	A	Algae or other aquatic plants 1.5m		img/l		1
	EC50	72h	A	lgae or other aquatic plants	37	37mg/l		1
	EC50	48h	С	rustacea	14	.6-21.5m	g/l	4
	Endpoint	Test Duration (hr) 5	Species	1	/alue		Source
	NOEC(ECx)			Fish	().01mg/L		2
p-tert-butylphen		72h		Algae or other aquatic plants		-2.4mg/l		2
	EC50	48h		Crustacea		3.4-4.5mg		4
	LC50	96h		Fish		>1mg/l	-	2
						-		

For benzyl alcohol: log Kow : 1.1Koc : <5Henry's atm m3 /mol: 3.91E-07BOD 5: 1.55-1.6,33-62%COD : 96%ThOD : 2.519BCF : 4 Bioaccumulation: Not significant

Anaerobic Effects: Significant degradation.

Effects on algae and plankton: Inhibits degradation of glucose

Degradation Biological: Significant processes

Abiotic: RxnOH*,no photochem

Ecotoxicity: Fish LC50 (48 h): fathead minnow 770 mg/l; (72 h): 480 mg/l; (96 h) 460 mg/l. Prevent, by any means available, spillage from entering drains or water courses. **DO NOT** discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
benzyl alcohol	LOW	LOW
4,4'- methylenebis(cyclohexylamine)	HIGH	HIGH
1,3- cyclohexanebis(methylamine)	LOW	LOW
2,6-di-tert-butyl-4-methylphenol	HIGH	HIGH
m-xylenediamine	HIGH	HIGH
isophorone diamine	HIGH	HIGH
p-tert-butylphenol	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation	
benzyl alcohol	LOW (LogKOW = 1.1)	
4,4'- methylenebis(cyclohexylamine)	LOW (LogKOW = 3.2649)	
1,3- cyclohexanebis(methylamine)	LOW (LogKOW = 1.0688)	
2,6-di-tert-butyl-4-methylphenol	HIGH (BCF = 2500)	
m-xylenediamine	LOW (BCF = 2.7)	
isophorone diamine	LOW (BCF = 3.4)	
p-tert-butylphenol	LOW (BCF = 240)	

Mobility in soil

Ingredient	Mobility	
benzyl alcohol	LOW (Log KOC = 15.66)	
4,4'- methylenebis(cyclohexylamine)	LOW (Log KOC = 672.4)	
1,3- cyclohexanebis(methylamine)	LOW (Log KOC = 914.6)	
2,6-di-tert-butyl-4-methylphenol	LOW (Log KOC = 23030)	
m-xylenediamine	LOW (Log KOC = 914.6)	
isophorone diamine	LOW (Log KOC = 340.4)	
p-tert-butylphenol	LOW (Log KOC = 1912)	

SECTION 13 Disposal considerations

Waste treatment methods

	-
Product / Packaging disposal	 Containers may still present a chemical hazard/ danger when empty. Return to supplier for reuse/ recycling if possible. Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. DO NOT allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal. Recycle wherever possible. Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.

SECTION 14 Transport information

Labels Required



Shipping container, transport vehicle placarding, and labeling may vary from the below information. This depends on the quantity shipped, the applicability of excepted quantity requirements, limited quantity requirements, and/or special provisions according to US DOT, IATA and IMDG regulations. In case of reshipment, it is the responsibility of the shipper to determine the appropriate labels and markings in accordance with applicable transport regulations.

Land transport (DOT)

14.1. UN number or ID number	2735	2735			
14.2. UN proper shipping name	Amines, liquid, corros	ines, liquid, corrosive, n.o.s. (contains isophorone diamine)			
14.3. Transport hazard class(es)	Class8Subsidiary HazardNot Applicable				
14.4. Packing group	Ш	III			
14.5. Environmental hazard	Environmentally haza	Environmentally hazardous			
14.6. Special precautions for user	Hazard Label Special provisions	8 IB3, T7, TP1, TP28			

Air transport (ICAO-IATA / DGR)

14.1. UN number	2735		
14.2. UN proper shipping name	Amines, liquid, corrosive, n.o.s. * (contains isophorone diamine)		
14.3. Transport hazard class(es)	ICAO/IATA Class	8	
	ICAO / IATA Subsidiary Hazard	Not Applicable	
	ERG Code	8L	

14.4. Packing group	Ш			
14.5. Environmental hazard	Environmentally hazardous			
	Special provisions	A3 A803		
	Cargo Only Packing Instructions			
14.6. Special	Cargo Only Maximum Qty / Pack	60 L		
precautions for	Passenger and Cargo Packing Instructions	852		
user	Passenger and Cargo Maximum Qty / Pack	5 L		
	Passenger and Cargo Limited Quantity Packing Instructions	Y841		
	Passenger and Cargo Limited Maximum Qty / Pack	1 L		

Sea transport (IMDG-Code / GGVSee)

14.1. UN number	2735			
14.2. UN proper shipping name	AMINES, LIQUID, CORROSIVE, N.O.S. (contains isophorone diamine)			
14.3. Transport hazard class(es)	IMDG Class IMDG Subsidiary Ha	azard	8 Not Applicable	
14.4. Packing group	III			
14.5 Environmental hazard	Marine Pollutant			
14.6. Special	EMS Number	F-A ,	S-B	
precautions for	Special provisions	223 2	74	
user	Limited Quantities	5 L		

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group	
benzyl alcohol	Not Available	
formaldehyde/ benzenamine, hydrogenated	Not Available	
4,4'- methylenebis(cyclohexylamine)	Not Available	
1,3- cyclohexanebis(methylamine)	Not Available	
2,6-di-tert-butyl-4-methylphenol	Not Available	
m-xylenediamine	Not Available	
isophorone diamine	Not Available	
p-tert-butylphenol	Not Available	

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type	
benzyl alcohol	Not Available	
formaldehyde/ benzenamine, hydrogenated	Not Available	
4,4'- methylenebis(cyclohexylamine)	Not Available	
1,3- cyclohexanebis(methylamine)	Not Available	
2,6-di-tert-butyl-4-methylphenol	Not Available	
m-xylenediamine	Not Available	
isophorone diamine	Not Available	
p-tert-butylphenol	Not Available	

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

benzyl alcohol is found on the following regulatory lists

US - Massachusetts - Right To Know Listed Chemicals

US AIHA Workplace Environmental Exposure Levels (WEELs)

US DOE Temporary Emergency Exposure Limits (TEELs)

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US Toxicology Excellence for Risk Assessment (TERA) Workplace Environmental Exposure Levels (WEEL)

formaldehyde/ benzenamine, hydrogenated is found on the following regulatory lists

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

4,4'-methylenebis(cyclohexylamine) is found on the following regulatory lists

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

1,3-cyclohexanebis(methylamine) is found on the following regulatory lists

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

2,6-di-tert-butyl-4-methylphenol is found on the following regulatory lists

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

US - Alaska Air Quality Control - Concentrations Triggering an Air Quality Episode for Air Pollutants Other Than PM-2.5

US - Massachusetts - Right To Know Listed Chemicals

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Permissible Exposure Limits (PELs) Table Z-1

US OSHA Permissible Exposure Limits (PELs) Table Z-3

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

m-xylenediamine is found on the following regulatory lists

US - Massachusetts - Right To Know Listed Chemicals

US NIOSH Recommended Exposure Limits (RELs)

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

isophorone diamine is found on the following regulatory lists

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

p-tert-butylphenol is found on the following regulatory lists

No

Novo Poxi Clear 'B'

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

US - Alaska Air Quality Control - Concentrations Triggering an Air Quality Episode for Air Pollutants Other Than PM-2.5

US DOE Temporary Emergency Exposure Limits (TEELs)

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Permissible Exposure Limits (PELs) Table Z-1

US OSHA Permissible Exposure Limits (PELs) Table Z-3

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

Additional Regulatory Information

Not Applicable

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 hazard categories

Flammable (Gases, Aerosols, Liquids, or Solids)

Flammable (Gases, Aelosols, Elquids, or Solids)	INU	
Gas under pressure		
Explosive	No	
Self-heating	No	
Pyrophoric (Liquid or Solid)	No	
Pyrophoric Gas	No	
Corrosive to metal	Yes	
Oxidizer (Liquid, Solid or Gas)	No	
Organic Peroxide	No	
Self-reactive	No	
In contact with water emits flammable gas	No	
Combustible Dust	No	
Carcinogenicity	Yes	
Acute toxicity (any route of exposure)	Yes	
Reproductive toxicity	Yes	
Skin Corrosion or Irritation	Yes	
Respiratory or Skin Sensitization	Yes	
Serious eye damage or eye irritation	Yes	
Specific target organ toxicity (single or repeated exposure)	Yes	
Aspiration Hazard	No	
Germ cell mutagenicity		
Simple Asphyxiant		
Hazards Not Otherwise Classified		

US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)

None Reported

US. EPCRA Section 313 Toxic Release Inventory (TRI) (40 CFR 372)

None Reported

Additional Federal Regulatory Information

Not Applicable

State Regulations

US. California Proposition 65

None Reported

Additional State Regulatory Information

Not Applicable

National Inventory Status

National Inventory	Status	
Australia - AIIC / Australia Non-Industrial Use	Yes	
Canada - DSL	Yes	
Canada - NDSL	No (benzyl alcohol; formaldehyde/ benzenamine, hydrogenated; 4,4'-methylenebis(cyclohexylamine); 1,3- cyclohexanebis(methylamine); m-xylenediamine; isophorone diamine; p-tert-butylphenol)	
China - IECSC	Yes	
Europe - EINEC / ELINCS / NLP	No (formaldehyde/ benzenamine, hydrogenated)	
Japan - ENCS	No (formaldehyde/ benzenamine, hydrogenated)	
Korea - KECI	Yes	
New Zealand - NZloC	Yes	
Philippines - PICCS	Yes	
USA - TSCA	Yes	
Taiwan - TCSI	Yes	
Mexico - INSQ	No (formaldehyde/ benzenamine, hydrogenated; 4,4'-methylenebis(cyclohexylamine); 1,3- cyclohexanebis(methylamine))	
Vietnam - NCI	Yes	
Russia - FBEPH	No (formaldehyde/ benzenamine, hydrogenated)	
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.	

SECTION 16 Other information

Revision Date	05/28/2024
Initial Date	06/19/2020

CONTACT POINT

PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES

SDS Version Summary

Version	Date of Update	Sections Updated
3.7	05/28/2024	Toxicological information - Acute Health (skin), Hazards identification - Classification, Composition / information on ingredients - Ingredients, Name

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

Definitions and abbreviations

- PC TWA: Permissible Concentration-Time Weighted Average
- + PC STEL: Permissible Concentration-Short Term Exposure Limit
- IARC: International Agency for Research on Cancer
- + ACGIH: American Conference of Governmental Industrial Hygienists
- STEL: Short Term Exposure Limit
- TEEL: Temporary Emergency Exposure Limit.
- IDLH: Immediately Dangerous to Life or Health Concentrations
- ES: Exposure Standard
- OSF: Odour Safety Factor
- NOAEL: No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- BCF: BioConcentration Factors
- BEI: Biological Exposure Index
- DNEL: Derived No-Effect Level
- PNEC: Predicted no-effect concentration
- + AIIC: Australian Inventory of Industrial Chemicals
- DSL: Domestic Substances List
- NDSL: Non-Domestic Substances List
- IECSC: Inventory of Existing Chemical Substance in China
- EINECS: European INventory of Existing Commercial chemical Substances
- ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
- ENCS: Existing and New Chemical Substances Inventory
- KECI: Korea Existing Chemicals Inventory
- NZIoC: New Zealand Inventory of Chemicals
- PICCS: Philippine Inventory of Chemicals and Chemical Substances
- TSCA: Toxic Substances Control Act
- TCSI: Taiwan Chemical Substance Inventory
- INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory
- + FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.

