

ICP Construction Inc.

Version No: 1.1

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Issue Date: 05/28/2024 Print Date: 05/29/2024 S.GHS.USA.EN

SECTION 1 Identification

Product Identifier		
Product name	CHEM-THANE P50 CLEAR 'A'	
Synonyms	Not Available	
Proper shipping name	Combustible liquid, n.o.s. (contains dipropylene glycol monomethyl ether acetate)	
Other means of identification	Not Available	

Recommended use of the chemical and restrictions on use

Relevant identified uses High Performance Coating

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	ICP Construction Inc.	
Address	50 Dascomb Road Andover, MA 01810 United States	
Telephone	1-866-667-5119 1-978-623-9987	
Fax	Not Available	
Website	www.icpgroup.com	
Email	sds@icpgroup.com	

Emergency phone number

Association / Organisation	ChemTel	
Emergency telephone numbers	1-800-255-3924	
Other emergency telephone numbers	1-813-248-0585	

SECTION 2 Hazard(s) identification

Classification of the substance or mixture

H319

Causes serious eye irritation.

NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification Flammable Liquids Category 4, Sensitisation (Skin) Category 1, Serious Eye Damage/Eye Irritation Category 2A, Hazardous to the Aquatic Environment Long-Term Hazard Category 3

Label elements	
Hazard pictogram(s)	
Signal word	Warning
Hazard statement(s)	
H227	Combustible liquid.
H317	May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Hazard(s) not otherwise classified

Not Applicable

Precautionary statement(s) Prevention

, , , , , , , , , , , , , , , , , , , ,	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves, protective clothing, eye protection and face protection.
P264	Wash all exposed external body areas thoroughly after handling.
P272	Contaminated work clothing must not be allowed out of the workplace.

Precautionary statement(s) Response

P370+P378	P370+P378 In case of fire: Use alcohol resistant foam or normal protein foam to extinguish.	
P302+P352	P302+P352 IF ON SKIN: Wash with plenty of water and soap.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.	
P337+P313	If eye irritation persists: Get medical advice/attention.	
P362+P364	Take off contaminated clothing and wash it before reuse.	

Precautionary statement(s) Storage

P403+P235 Store in a well-ventilated place. Keep cool.

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
136210-32-7	15-40	aspartic acid, N,N'-(methylenedicyclohexanediyl)bis-,ester
623-91-6*	1-5	Aliphatic carboxylic ester
136210-30-5	15-40	aspartic acid, N.N-(methylenedicyclohexanediyl)bis-,ester
145899-78-1	1-5	3-oxazolidineethanol, 2-(1-methylethyl)-, carbonate (2:1)
88917-22-0*	7-13	dipropylene glycol monomethyl ether acetate
108-83-8	1-5	diisobutyl ketone

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 First-aid measures

Description of first aid measures

Eye Contact	 If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	
Ingestion Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor. 	

Most important symptoms and effects, both acute and delayed

See Section 11

Indication of any immediate medical attention and special treatment needed Treat symptomatically.

Extinguishing media

- Foam.
- Dry chemical powder.
 BCF (where regulations permit).

Special hazards arising from the substrate or mixture

Fire Incompatibility Avoid	contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Special protective equipment and precautions for fire-fighters

F	Fire Fighting	
Fire/Explo	sion Hazard	 Combustible. Slight fire hazard when exposed to heat or flame. Heating may cause expansion or decomposition leading to violent rupture of containers. Combustion products include: carbon dioxide (CO2) nitrogen oxides (NOx) other pyrolysis products typical of burning organic material.

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment.
Major Spills	

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling	
Safe handling	DO NOT allow clothing wet with material to stay in contact with skin
Other information	Consider storage under inert gas.

Conditions for safe storage, including any incompatibilities

Suitable container	
Storage incompatibility	 Segregate from alcohol, water. Avoid reaction with oxidising agents

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Limits (PELs) Table Z-1	diisobutyl ketone	Diisobutyl ketone	50 ppm / 290 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	diisobutyl ketone	Diisobutyl ketone	25 ppm / 150 mg/m3	Not Available	Not Available	Not Available

Emergency Limits

Ingredient	TEE	L-1	TEEL-2		TEEL-3
diisobutyl ketone	75 p	om	330 ppm		2000* ppm
Ingredient		Original IDLH		Revised IDL	н
aspartic acid, N,N'- (methylenedicyclohexanediyl)bis-,ester		Not Available		Not Available	
Aliphatic carboxylic ester		Not Available		Not Available	
aspartic acid, N,N'- (methylenedicyclohexanediyl)bis-,ester		Not Available		Not Available	
3-oxazolidineethanol, 2-(1- methylethyl)-, carbonate (2:1)		Not Available		Not Available	
dipropylene glycol monomethyl ether		Not Available		Not Available	

Ingredient	Original IDLH	Revised IDLH	
acetate			
diisobutyl ketone	500 ppm	Not Available	
Occupational Exposure Banding			
Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit	
aspartic acid, N,N'- (methylenedicyclohexanediyl)bis-,ester	D	> 0.1 to ≤ 1 ppm	
Aliphatic carboxylic ester	E	≤ 0.1 ppm	
aspartic acid, N,N'- (methylenedicyclohexanediyl)bis-,ester	D	> 0.1 to ≤ 1 ppm	
3-oxazolidineethanol, 2-(1- methylethyl)-, carbonate (2:1)	D	> 0.1 to ≤ 1 ppm	
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.		

Exposure controls

Appropriate engineering controls	
Individual protection measures, such as personal protective equipment	
Eye and face protection	 Safety glasses with side shields. Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent] Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants.
Skin protection	See Hand protection below
Hands/feet protection	 Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber NOTE: The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.
Body protection	See Other protection below
Other protection	

Respiratory protection

Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
 The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Not Available			
Physical state	Liquid	Relative density (Water = 1)	8.65	
Odour	Not Available	Partition coefficient n-octanol / water	Not Available	
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available	
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available	
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available	
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available	
Flash point (°C)	>86	Taste	Not Available	
Evaporation rate	Not Available	Explosive properties	Not Available	
Flammability	Combustible.	Oxidising properties	Not Available	

Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	12

SECTION 10 Stability and reactivity

Reactivity
Chemical stability
Possibility of hazardous reactions
Conditions to avoid
Incompatible materials
Hazardous decomposition products
Conditions to avoid Incompatible materials Hazardous decomposition

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
Ingestion	The material has NOT been classified by EC Directives or other classification systems as 'harmful by ingestion'. This is because of the lack of corroborating animal or human evidence. High molecular weight material; on single acute exposure would be expected to pass through gastrointestinal tract with little change / absorption. Occasionally accumulation of the solid material within the alimentary tract may result in formation of a bezoar (concretion), producing discomfort.
Skin Contact	Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. There is some evidence to suggest that this material can cause inflammation of the skin on contact in some persons. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	This material can cause eye irritation and damage in some persons.
Chronic	Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. Some glycol esters and their ethers cause wasting of the testicles, reproductive changes, infertility and changes to kidney function. Shorter chain compounds are more dangerous. This material contains a substantial amount of polymer considered to be of low concern. These are classified under having MWs of between 1000 to 10000 with less than 25% of molecules with MWs under 1000 and less than 10% under 500; or having a molecular weight average of over 10000. Sensitisation may result in allergic dermatitis responses including rash, itching, hives or swelling of extremities.

CHEM-THANE P50 CLEAR 'A'	ΤΟΧΙΟΙΤΥ	IRRITATION		
	Not Available		Not Available	
	ΤΟΧΙCΙΤΥ	IRRI	IRRITATION	
	dermal (rat) LD50: >2000 mg/kg ^[2]	Eye	Eye : Mild	
aspartic acid, N,N'- (methylenedicyclohexanediyl)bis-,ester	Inhalation (Rat) LC50: >4.224 mg/L4h ^[1]	Eye:	Eye: no adverse effect observed (not irritating) ^[1]	
	Oral (Rat) LD50: >2000 mg/kg ^[2]	Skin	Skin : Moderate	
		Skin	Skin: no adverse effect observed (not irritating) ^[1]	
	ΤΟΧΙΟΙΤΥ			IRRITATION
Aliphatic carboxylic ester	Oral (Mouse) LD50; 2227 mg/kg ^[2]		Not Available	
	Oral (Rat) LD50: 1780 mg/kg ^[2]			
aspartic acid, N,N'-				
aspartic acid, N,N- (methylenedicyclohexanediyl)bis-,ester	ΤΟΧΙCITY	IRRI	TATION	
	dermal (rat) LD50: >2000 mg/kg ^[2]	rat) LD50: >2000 mg/kg ^[2] Eye : Mild		
	Inhalation (Rat) LC50: >4.224 mg/L4h ^[1] Eye: no adverse effect observed (not irritating) ^[1]		ed (not irritating) ^[1]	
	Oral (Rat) LD50: >2000 mg/kg ^[2]	00 mg/kg ^[2] Skin : Moderate		
	Skin: no adverse effect observed (not irritating) ^[1]		ed (not irritating) ^[1]	

	L		1		
	тохіс	ΙТΥ		IRRITATION	
3-oxazolidineethanol, 2-(1-	dermal	(rat) LD50: >2000 mg/kg ^[2]		Not Available	
methylethyl)-, carbonate (2:1)		(at) LD50: >2000 mg/kg ^[2]			
	ΤΟΧΙΟ	ΙТΥ	IRRITATION		
dipropylene glycol monomethyl ether acetate	Dermal	l (rabbit) LD50: >5000 mg/kg* ^[2]	Eye: no adverse effect observ	Eye: no adverse effect observed (not irritating) ^[1]	
	Oral (R	at) LD50: >5000 mg/kg* ^[2]	Skin: no adverse effect observ	Skin: no adverse effect observed (not irritating) ^[1]	
	TOXICITY dermal (rat) LD50: >2000 mg/kg ^[1]				
			Eye (human): 25 ppm/15min -	miid	
		ion (Rat) LC50: >14.5 mg/l4h ^[1]	Eye (rabbit): 500 mg		
	Oral (R	at) LD50: >2000 mg/kg ^[1]	Eye: no adverse effect observ Skin (g.pig): repeated - SEVEI		
diisobutyl ketone			Skin (g.pig): Strong *		
			Skin (rabbit): 10 mg/24h - mild		
			Skin (rabbit): 500 mg - mild		
			Skin: adverse effect observed	(irritating) ^[1]	
			Skin: no adverse effect observ		
ASPARTIC ACID, N,N'- (METHYLENEDICYCLOHEXANEDIYL)BIS-,ESTER			ed essentially by allergen specific immune may be involved. Such allergy is of the de		
Aliphatic carboxylic ester		Repeat dose toxicity: In an oral combined repeated dose and reproductive/developmental toxicity test at doses of 0, 11, 30 and 100 mg/kg/day [OECD TG 422], no effects were observed on clinical signs, body weight, food consumption, urinalysis, haematology or blood chemistry examinations. Histopathological examination of the forestomach revealed thickening of the mucosal layer in both sexes of all treated groups, hyperkeratosis in males of all treated groups and in females of the 30 and 100 mg/kg groups. These changes were dose-dependent.			
3-OXAZOLIDINEETHANOL, 2-(1- METHYLETHYL)-, CARBONATE (2:1)		* Industrial Copolymers Limited SDS			
dipropylene glycol monomethyl ether acetate		For propylene glycol ethers (PGEs): Typical propylene glycol ethers include propylene glycol n-butyl ether (PnB); dipropylene glycol n-butyl ether (DPnB); dipropylene glycol methyl ether acetate (DPMA) and tripropylene glycol methyl ether (TPM). Testing of a wide variety of propylene glycol ethers has shown that propylene glycol-based ethers are less toxic than some ethers of the ethylene series. The common toxicities associated with the lower molecular weight homologues of the ethylene series, such as adverse effects on the reproductive organs, the developing embryo and foetus, blood or thymus gland, are not seen with the commercial-grade propylene glycol ethers. In the ethylene series, metabolism of the terminal hydroxyl group produces and alkoxyacetic acid.			
DIISOBUTYL KETONE		[Eastman; * for mixed isomer, ** for 2,6-dimethyl-4-heptanone] NOEL = 400 ppm (12 exposures rat) * LOEL = 250 ppm (30 exposures, rat) ** NOEL = 125 ppm (''') ** - target organ; kidney LOEL = 2000 mg/kg/day (oral neurotoxicity; minor target organs - liver, kidney, stomach) ** NOEL = 2000 mg/kg (for neurotoxicity) ** Skin sensitisation (g.pig) - moderate * For diisobutyl ketone (DIBK) There is very little data on DIBK exposure available. For the risk characterisation a selection of the data on methyl isobutyl ketone (MIBK) and methyl ethyl ketone, (MEK) was used. MEK and MIBK were selected be cause they are comparable to DIBK in effects and use. The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.			
CHEM-THANE P50 CLEAR 'A' & ASPARTIC		-			
N,N'- (METHYLENEDICYCLOHEXANEDIYL)BIS-,ESTER & 3-OXAZOLIDINEETHANOL, 2-(1- METHYLETHYL)-, CARBONATE (2:1)		The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type.			
ASPARTIC ACID, N,N'- (METHYLENEDICYCLOHEXANEDIYL)BIS-,ESTER		observed in 85% of the test substanc was observed in 50% and 35% of the respectively. A scaly administration s 1000 mg/kg/day * Genotoxicity ? bac Genotoxicity ? in vivo erythrocyte mid acute toxicity via the oral, dermal and slight skin and eye irritant and mild re animals at a concentration of 50%, th sensitisation cannot be ruled out. Re Level (NOAEL) was established as 1 Mutagenicity. The material was nega not considered to be mutagenic. Neu intraperitoneal administration of a fail	est) * After the first challenge very mild to be animals. After the second challenge, we a test substance animals challenged with a ite was observed in some animals. Rat re- terial reverse mutation non mutagenic * C cronucleus test non clastogenic * The noti d inhalation routes. Irritation and Sensitisa espiratory irritant and a skin sensitiser. As a substance is considered to be a strong peated Dose Toxicity. In a 28 day study in 000 mg/kg bw/day based on the absence tive in an Ames test and an in vivo erythror trotoxicity: In the in vivo mouse erythrocytr rly high dose (5345 mg/kg bw) some evid was not observed in any of the tests conc	ery mild to clearly visible skin reddening 25% and 12% test substance peat dose oral toxicity - 29 days NOAEL Senotoxicity ? in vitro not determined * fied chemical is considered to be of low tion. The material is considered to be a skin reactions were observed in 85% of sensitiser. The potential for respiratory rats, the No Observed Adverse Effect of adverse treatment related effects. cocyte micronucleus test. The substance is e micronucleus test, following ence of non-specific neurological	

		either be species-specific or an expression of generalised toxicity indu- neurotoxicity. * NICNAS Report Allergic reactions involving the respiratory tract are usually due to inte and occur rapidly. Allergic potential of the allergen and period of expo Some people may be genetically more prone than others, and exposu Attention should be paid to atopic diathesis, characterised by increase and eczema.	eractions between IgE antibodies and allergens sure often determine the severity of symptoms. ure to other irritants may aggravate symptoms.	
dipropylene glycol monomethyl ether acetate & DIISOBUTYL KETONE		Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant.		
Acute Toxicity	×	Carcinogenicity	×	
Skin Irritation/Corrosion	×	Reproductivity	×	
Serious Eye Damage/Irritation	✓ STOT - Single Exposure		×	
Respiratory or Skin sensitisation	STOT - Repeated Exposure		×	
Mutagenicity	×	Aspiration Hazard	×	
		Legend: X – Data either not a	vailable or does not fill the criteria for classification	

SECTION 12 Ecological information

Toxicity Endpoint Test Duration (hr) Species Value Source CHEM-THANE P50 CLEAR 'A' Not Available Not Available Not Available Not Available Not Available Endpoint Test Duration (hr) Species Value Source LC50 96h Fish 66mg/l 2 aspartic acid, N,N'-72h EC50 Algae or other aquatic plants 34mg/l 2 (methylenedicyclohexanediyl)bis-,ester EC50 48h Crustacea 88.6ma/l Not Available NOEC(ECx) 48h Crustacea Not Available 10mg/l Test Duration (hr) Value Endpoint Species Source Aliphatic carboxylic ester LC50 96h Fish 4.5mg/L Δ NOEC(ECx) 0.82h Algae or other aquatic plants >=250mg/l 4 Endpoint Test Duration (hr) Species Value Source LC50 96h Fish 66mg/l 2 aspartic acid, N,N'-EC50 72h Algae or other aquatic plants 34mg/l 2 (methylenedicyclohexanediyl)bis-,ester FC50 48h Crustacea 88.6ma/l Not Available NOEC(ECx) 48h Crustacea 10mg/l Not Available Endpoint Test Duration (hr) Species Value Source LC50 96h Fish 87500mg/L Not Available 3-oxazolidineethanol, 2-(1methylethyl)-, carbonate (2:1) EC50 48h Crustacea >100mg/l Not Available EC50(ECx) Not Available 48h Crustacea >100mg/l Endpoint Test Duration (hr) Value Source Species 62.5mg/l NOEC(ECx) 96h Fish 2 dipropylene glycol monomethyl ether EC50 72h Algae or other aquatic plants >100mg/l 2 acetate EC50 48h Crustacea 1090mg/l 2 LC50 96h Fish 110.55mg/l 2 Endpoint Test Duration (hr) Species Value Source EC50 72h Algae or other aquatic plants 26.3mg/l 2 LC50 96h Fish 30mg/l 2 diisobutyl ketone EC50 48h Crustacea 250mg/l 1 NOEC(ECx) 96h Algae or other aquatic plants 46mg/l 1 EC50 96h Algae or other aquatic plants 100mg/l 1

Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

For Propylene Glycol Ethers: log Kow's range from 0.309 for TPM to 1.523 for DPnB. Calculated BCFs range from 1.47 for DPnB to 3.16 for DPMA and TPM, indicating low bioaccumulation. Henry's Law Constants are low for all category members, ranging from 5.7 x 10-9 atm-m3/mole for TPM to 2.7 x10-9 atm-m3/mole for PnB. For high molecular weight synthetic polymers: (according to the Sustainable Futures (SF) program (U.S. EPA 2005b; U.S. EPA 2012c) polymer assessment guidance.)

High MW polymers are expected:

 \cdot to have low vapour pressure and are not expected to undergo volatilization .

· to adsorb strongly to soil and sediment

· to be non-biodegradable (not anticipated to be assimilated by microorganisms.- therefore, biodegradation is not expected to be an important removal process. However many exceptions exist

High MW polymers are not expected to undergo removal by other degradative processes under environmental conditions

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
Aliphatic carboxylic ester	LOW	LOW
dipropylene glycol monomethyl ether acetate	HIGH	HIGH
diisobutyl ketone	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
Aliphatic carboxylic ester	LOW (LogKOW = 2.1955)
dipropylene glycol monomethyl ether acetate	LOW (LogKOW = 0.6595)
diisobutyl ketone	LOW (LogKOW = 2.5646)

Mobility in soil

Ingredient	Mobility
Aliphatic carboxylic ester	LOW (Log KOC = 10.9)
dipropylene glycol monomethyl ether acetate	LOW (Log KOC = 10)
diisobutyl ketone	LOW (Log KOC = 60.12)

SECTION 13 Disposal considerations

Product / Packaging disposal	 Containers may still present a chemical hazard/ danger when empty. Return to supplier for reuse/ recycling if possible. Otherwise: If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating i their area. In some areas, certain wastes must be tracked. DO NOT allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal.
	In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.

SECTION 14 Transport information

Labels Required	
Marine Pollutant	NO

Shipping container, transport vehicle placarding, and labeling may vary from the below information. This depends on the quantity shipped, the applicability of excepted quantity requirements, limited quantity requirements, and/or special provisions according to US DOT, IATA and IMDG regulations. In case of reshipment, it is the responsibility of the shipper to determine the appropriate labels and markings in accordance with applicable transport regulations.

Land transport (DOT)

14.1. UN number or ID number	NA1993		
14.2. UN proper shipping name	Combustible liquid, n.c	Combustible liquid, n.o.s. (contains dipropylene glycol monomethyl ether acetate)	
14.3. Transport hazard class(es)	Class Subsidiary Hazard	Comb liq Not Applicable	
14.4. Packing group	II		
14.5. Environmental hazard	Not Applicable		
14.6. Special precautions for user	Hazard Label Special provisions	Not Applicable 148, IB3, T1, TP1	

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
aspartic acid, N,N'- (methylenedicyclohexanediyl)bis-,ester	Not Available
Aliphatic carboxylic ester	Not Available
aspartic acid, N,N'- (methylenedicyclohexanediyl)bis-,ester	Not Available
3-oxazolidineethanol, 2-(1- methylethyl)-, carbonate (2:1)	Not Available
dipropylene glycol monomethyl ether acetate	Not Available
diisobutyl ketone	Not Available

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
aspartic acid, N,N'- (methylenedicyclohexanediyl)bis-,ester	Not Available
Aliphatic carboxylic ester	Not Available
aspartic acid, N,N'- (methylenedicyclohexanediyl)bis-,ester	Not Available
3-oxazolidineethanol, 2-(1- methylethyl)-, carbonate (2:1)	Not Available
dipropylene glycol monomethyl ether acetate	Not Available
diisobutyl ketone	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

aspartic acid, N,N'-(methylenedicyclohexanediyl)bis-,ester is found on the following regulatory lists US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

Aliphatic carboxylic ester is found on the following regulatory lists

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

aspartic acid, N,N'-(methylenedicyclohexanediyl)bis-,ester is found on the following regulatory lists US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

3-oxazolidineethanol, 2-(1-methylethyl)-, carbonate (2:1) is found on the following regulatory lists US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

dipropylene glycol monomethyl ether acetate is found on the following regulatory lists

US - California Hazardous Air Pollutants Identified as Toxic Air Contaminants US Clean Air Act - Hazardous Air Pollutants

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

diisobutyl ketone is found on the following regulatory lists

US - Massachusetts - Right To Know Listed Chemicals

US DOE Temporary Emergency Exposure Limits (TEELs)

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Permissible Exposure Limits (PELs) Table Z-1

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

Additional Regulatory Information

Not Applicable

Federal Regulations

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 hazard categories

Flammable (Gases, Aerosols, Liquids, or Solids)	Yes
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No

Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	No
Acute toxicity (any route of exposure)	No
Reproductive toxicity	No
Skin Corrosion or Irritation	No
Respiratory or Skin Sensitization	Yes
Serious eye damage or eye irritation	Yes
Specific target organ toxicity (single or repeated exposure)	No
Aspiration Hazard	No
Germ cell mutagenicity	No
Simple Asphyxiant	No
Hazards Not Otherwise Classified	No

US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4) None Reported

US. EPCRA Section 313 Toxic Release Inventory (TRI) (40 CFR 372) None Reported

Additional Federal Regulatory Information

Not Applicable

State Regulations

US. California Proposition 65

None Reported

Additional State Regulatory Information

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non- Industrial Use	Yes
Canada - DSL	No (Aliphatic carboxylic ester; 3-oxazolidineethanol, 2-(1-methylethyl)-, carbonate (2:1))
Canada - NDSL	No (aspartic acid, N,N'-(methylenedicyclohexanediyl)bis-,ester; aspartic acid, N,N'-(methylenedicyclohexanediyl)bis-,ester; dipropylene glycol monomethyl ether acetate; diisobutyl ketone)
China - IECSC	No (3-oxazolidineethanol, 2-(1-methylethyl)-, carbonate (2:1))
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	No (aspartic acid, N,N'-(methylenedicyclohexanediyl)bis-,ester; aspartic acid, N,N'-(methylenedicyclohexanediyl)bis-,ester; 3- oxazolidineethanol, 2-(1-methylethyl)-, carbonate (2:1); dipropylene glycol monomethyl ether acetate)
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	No (aspartic acid, N,N'-(methylenedicyclohexanediyl)bis-,ester; aspartic acid, N,N'-(methylenedicyclohexanediyl)bis-,ester; 3- oxazolidineethanol, 2-(1-methylethyl)-, carbonate (2:1))
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	No (aspartic acid, N,N-(methylenedicyclohexanediyl)bis-,ester; aspartic acid, N,N'-(methylenedicyclohexanediyl)bis-,ester; 3- oxazolidineethanol, 2-(1-methylethyl)-, carbonate (2:1); dipropylene glycol monomethyl ether acetate)
Vietnam - NCI	Yes
Russia - FBEPH	No (3-oxazolidineethanol, 2-(1-methylethyl)-, carbonate (2:1); dipropylene glycol monomethyl ether acetate)
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	05/28/2024
Initial Date	08/12/2019

CONTACT POINT

PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references. The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios.